

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : Hospec THICK BLEACH 5 Litres Product code : 3003825.

1.2. Relevant identified uses of the substance or mixture and uses advised against Product Type : Toilet Cleaner

1.3. Details of the supplier of the safety data sheet

Registered company name : McBride Plc Middleton.

Address : Middleton Way, Middleton.M24 4DP.Manchester.UK.

Telephone : + 44 (0) 161 653 9037. Fax : .

MSDS@mcbride.co.uk

www.detergentinfo.com

1.4. Emergency telephone number : + 44 (0) 161 653 9037.

Association/Organisation : .

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Substance that is corrosive to metals, Category 1 (Met. Corr. 1, H290).

Skin corrosion, Category 1A (Skin Corr. 1A, H314).

Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Corrosive (C, R 35).

Aquatic environmental hazard, chronic toxicity: toxic (N, R 51/53).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

2.2. Label elements

Biocidal detergent mixture (see section 15).

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS05 GHS09 Signal Word : DANGER Product identifiers : EC 231-668-3 SODIUM HYPOCHLORITE, SOLUTION CLACTIVE ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (>1 <2.5 MOL EO) (SODIUM EC 500-234-8 LAURETH/PARETH SULFATE) 011-002-00-6 SODIUM HYDROXIDE Additional labeling : EUH206 Warning! Do not use together with other products. May release dangerous gases (chlorine). Hazard statements : H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. H411 Toxic to aquatic life with long lasting effects. Precautionary statements - General : P101 If medical advice is needed, have product container or label at hand.

	Keep out of reach of children.
	Read label before use.
utionary statements - Prev	vention :
	Keep only in original container.
	Avoid release to the environment.
	Wear protective gloves/eye protection.
utionary statements - Resp	ponse :
+ P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
+ P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	Immediately call a POISON CENTER/doctor/

P391 Collect spillage.

Precautionary statements - Storage :

P405 Store locked up.

Precautionary statements - Disposal :

Dispose of contents/container in accordance with local requirements for domestic waste disposal.

2.3. Other hazards

P102
P103
Preca
P234
P273
P280
Preca
P303
P305

P310

P501

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

$\begin{array}{ c c c c c c c c c c c c c c c c c c c$	Composition :				
$\begin{array}{c c c c c c c c c c c c c c c c c c c $	Identification	(EC) 1272/2008	67/548/EEC	Note	%
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	INDEX: 017_011_00_1	GHS05, GHS09		В	2.5 <= x % < 10
$\begin{array}{c c c c c c c c c c c c c c c c c c c $	CAS: 7681-52-9	Dgr	C;R34		
SODIUM HYPOCHLORITE, SOLUTION CL ACTIVEAquatic Acute 1, H400 M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 1 EUH:031R31Image: Close of the second	EC: 231-668-3	Met. Corr. 1, H290			
SODIUM HYPOCHLORITE, SOLUTION CL ACTIVE M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 1 EUH:031 $Aquatic Chronic 1, H410$ M Sin Irit. 2, H315 R52/53 $aquatic Chronic 3, H412$ aq	REACH: 01-2119488154-34-xxxx	Skin Corr. 1B, H314	N;R50		
$\begin{array}{c c c c c c c c c c c c c c c c c c c $		Aquatic Acute 1, H400	R31		
$\begin{array}{ c c c c c c c c c c c c c c c c c c c$	SODIUM HYPOCHLORITE, SOLUTION CL	M Acute = 10			
EUH:031EUH:031INDEX: 1001548GHS05XiCAS: 68891-38-3DgrXi;R38-R41EC: 500-234-8Skin Irrit. 2, H315R52/53REACH: 01-2119488639-16-Eye Dam. 1, H318ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (>1 < 2.5 MOL EO) (SODIUM LAURETH/PARETH SULFATE)Aquatic Chronic 3, H412INDEX: 011-002-00-6GHS05C DgrCAS: 1310-73-2DgrEC: 215-185-5Skin Corr. 1A, H314REACH: 01-2119457892-27-GHS07, GHS05, GHS09 DgrSODIUM HYDROXIDEGHS07, GHS05, GHS09 DgrINDEX: 1001240GHS07, GHS05, GHS09 DgrCAS: 61788-90-7GHS07, GHS05, GHS09 DgrEC: 263-016-9Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Irrit. 2, H315 Skin Irrit. 2, H315 Skin Irrit. 2, H315 Skin Irrit. 2, H318 Aquatic Acute 1, H400	ACTIVE	Aquatic Chronic 1, H410			
$\begin{array}{ c c c c c c c c c c c c c c c c c c c$		M Chronic $= 1$			
$\begin{array}{cccc} CAS: 68891-38-3 & & Dgr & & Xi;R38-R41 \\ EC: 500-234-8 & & Skin Irrit. 2, H315 \\ EYe Dam. 1, H318 \\ Aquatic Chronic 3, H412 \\ \\ ALCOHOLS, C12-14, ETHOXYLATED, \\ SULFATES, SODIUM SALTS (>1 < 2.5 MOL \\ EO) (SODIUM LAURETH/PARETH SULFATE) \\ \hline NDEX: 011-002-00-6 & & GHS05 \\ CAS: 1310-73-2 & & Dgr & & C \\ CAS: 1310-73-2 & & Dgr & & C \\ EC: 215-185-5 & & Skin Corr. 1A, H314 \\ REACH: 01-2119457892-27- & & Skin Corr. 1A, H314 \\ REACH: 01-2119457892-27- & & Dgr & & Xn,N \\ SODIUM HYDROXIDE & & & & & & & & & & & & & & & & & & &$		EUH:031			
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	INDEX: 1001548	GHS05	Xi		0 <= x % < 2.5
$\begin{array}{c c c c c c c c c c c c c c c c c c c $	CAS: 68891-38-3	Dgr	Xi;R38-R41		
Aquatic Chronic 3, H412Aquatic Chronic 3, H412ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (>1 <2.5 MOL EO) (SODIUM LAURETH/PARETH SULFATE) A INDEX: 011-002-00-6 CAS: 1310-73-2GHS05 Dgr Skin Corr. 1A, H314CEC: 215-185-5 REACH: 01-2119457892-27-GHS07, GHS05, GHS09 DgrC, R35SODIUM HYDROXIDEGHS07, GHS05, GHS09 DgrXn,NINDEX: 1001240 CAS: 61788-90-7 EC: 263-016-9GHS07, GHS05, GHS09 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400Xn,N	EC: 500-234-8	Skin Irrit. 2, H315	R52/53		
ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (>1 <2.5 MOL EO) (SODIUM LAURETH/PARETH SULFATE)Image: Constraint of the second se	REACH: 01-2119488639-16-	Eye Dam. 1, H318			
SULFATES, SODIUM SALTS (>1 <2.5 MOL EO) (SODIUM LAURETH/PARETH SULFATE) Image: Constraint of the second		Aquatic Chronic 3, H412			
EO) (SODIUM LAURETH/PARETH SULFATE) C [1] 0 <= x % < 2.5	ALCOHOLS, C12-14, ETHOXYLATED,				
INDEX: 011-002-00-6 CAS: 1310-73-2 EC: 215-185-5 REACH: 01-2119457892-27- GHS05 Dgr Skin Corr. 1A, H314 C C;R35 [1] 0 <= x % < 2.5 SODIUM HYDROXIDE Skin Corr. 1A, H314 C;R35 0 <= x % < 2.5	SULFATES, SODIUM SALTS (>1 <2.5 MOL				
CAS: 1310-73-2 Dgr C;R35 C;R35 EC: 215-185-5 Skin Corr. 1A, H314 C;R35 C SODIUM HYDROXIDE GHS07, GHS05, GHS09 Xn,N 0 <= x % < 2.5	EO) (SODIUM LAURETH/PARETH SULFATE)			
EC: 215-185-5 REACH: 01-2119457892-27- SODIUM HYDROXIDE GHS07, GHS05, GHS09 INDEX: 1001240 GHS07, GHS05, GHS09 CAS: 61788-90-7 Dgr EC: 263-016-9 Acute Tox. 4, H302 Skin Irrit. 2, H315 N;R50 AMINES, COCO ALKYLDIMETHYL, Eye Dam. 1, H318 N-OXIDES Aquatic Acute 1, H400	INDEX: 011-002-00-6	GHS05	С	[1]	0 <= x % < 2.5
REACH: 01-2119457892-27- SODIUM HYDROXIDE INDEX: 1001240 GHS07, GHS05, GHS09 Xn,N CAS: 61788-90-7 Dgr Xn;R22 EC: 263-016-9 Acute Tox. 4, H302 Xi;R38-R41 Skin Irrit. 2, H315 N;R50 AMINES, COCO ALKYLDIMETHYL, Eye Dam. 1, H318 N-OXIDES Aquatic Acute 1, H400	CAS: 1310-73-2	Dgr	C;R35		
SODIUM HYDROXIDE GHS07, GHS05, GHS09 Xn,N 0 <= x % < 2.5 INDEX: 1001240 GHS07, GHS05, GHS09 Xn,N 0 <= x % < 2.5	EC: 215-185-5	Skin Corr. 1A, H314			
INDEX: 1001240 GHS07, GHS05, GHS09 Xn,N 0 <= x % < 2.5 CAS: 61788-90-7 Dgr Xn;R22 Xi;R38-R41 0 <= x % < 2.5	REACH: 01-2119457892-27-				
INDEX: 1001240 GHS07, GHS05, GHS09 Xn,N 0 <= x % < 2.5 CAS: 61788-90-7 Dgr Xn;R22 Xi;R38-R41 0 <= x % < 2.5					
CAS: 61788-90-7 Dgr Xn;R22 EC: 263-016-9 Acute Tox. 4, H302 Xi;R38-R41 Skin Irrit. 2, H315 N;R50 AMINES, COCO ALKYLDIMETHYL, Eye Dam. 1, H318 N-OXIDES Aquatic Acute 1, H400	SODIUM HYDROXIDE				
EC: 263-016-9Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400Xi;R38-R41 N;R50	INDEX: 1001240	GHS07, GHS05, GHS09	Xn,N		0 <= x % < 2.5
AMINES, COCO ALKYLDIMETHYL, N-OXIDESSkin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400N;R50	CAS: 61788-90-7	Dgr	Xn;R22		
AMINES, COCO ALKYLDIMETHYL, N-OXIDES Eye Dam. 1, H318 Aquatic Acute 1, H400	EC: 263-016-9	Acute Tox. 4, H302	Xi;R38-R41		
N-OXIDES Aquatic Acute 1, H400		Skin Irrit. 2, H315	N;R50		
	AMINES, COCO ALKYLDIMETHYL,	Eye Dam. 1, H318			
	N-OXIDES	Aquatic Acute 1, H400			

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of splashes or contact with eyes :

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

In the event of splashes or contact with skin :

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

Seek medical attention immediately, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO2)
- chlorine (Cl2)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

6.3. Methods and material for containment and cleaning up

Neutralise with an acidic decontaminant.

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDI	INC AND STOP	PACE					
Requirements relati			ncilities where	the mixture is he	ndlad		
		lises apply to all I	actitutes where	the mixture is na	nulea.		
7.1. Precautions for	0						
Always wash hands	e						
Remove and wash c		-	-	. ,.			
Remove contaminat	e 1			0 0		1	
Emergency showers	s and eye wash stat	tions will be requi	red in facilities	s where the mixtu	re is handled o	constantly.	
Fire prevention :							
Prevent access by u	-						
Recommended equip	-						
For personal protec							
Observe precaution	s stated on label ar	nd also industrial	safety regulation	ons.			
Prohibited equipment	-						
No smoking, eating			ure is used.				
Never open the pac	kages under pressu	ire.					
7.2. Conditions for s No data available.	afe storage, inclue	ding any incomp	atibilities				
Storage							
Keep out of reach o	f children.						
Keep the container		dry place.					
Packaging							
Always keep in pac	kaging made of an	identical materia	l to the original	1			
7.3. Specific end use	0 0	nuclinear materia	r to the origina	•			
No data available.	(3)						
ivo data available.							
SECTION 8 : EXPOS	URE CONTROL	S/PERSONAL P	PROTECTION	Ň			
8.1. Control parame	ters						
Occupational exposu	re limits :						
- ACGIH TLV (Am	erican Conference	of Governmental	Industrial Hyg	gienists, Threshol	d Limit Value	s, 2010) :	
CAS	TWA :	STEL:	Ceiling :	Definition :	Criteria :		
1310-73-2	-	-	2 mg/m3	-	-		
- France (INRS - El	D984 :2008) :						
CAS	VME-ppm :	VME-mg/m3:	VLE-ppm :	VLE-mg/m3:	Notes :	TMP No :	
1310-73-2	-	2	-	-	-	-	
- UK / WEL (Work	place exposure lim	nits, EH40/2005, 2	2007):				
CAS	TWA :	STEL:	Ceiling :	Definition :	Criteria :		
1310-73-2	-	2 mg/m3	-	-	-		
8.2. Exposure contro	ols	-					
Personal protection		s personal protec	tive equinmen	t			
=	ticasul es, such as						

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

- PVC (polyvinyl chloride)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Wear suitable protective clothing, in particular overalls and boots. These items must be kept in good condition and cleaned after use.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :			
Physical state :	Viscous liquid.		
Important health, safety and environmental information			
pH :	Not stated.		
	Strongly basic.		
Boiling point/boiling range :	Not specified.		
Flash point interval :	Not relevant.		
Vapour pressure (50°C) :	Not relevant.		
Density :	± 1.08		
Water solubility :	Soluble.		
Melting point/melting range :	Not specified.		
Self-ignition temperature :	Not specified.		
Decomposition point/decomposition range :	Not specified.		
Colour : Characteristic			
Odour : Characteristic			
9.2. Other information			
NT 1.2 111			

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

Mixture which by chemical action can corrode and even destroy metals.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :

- frost

10.5. Incompatible materials

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO2)

- chlorine (Cl2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure for up to three minutes.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

11.1.1. Substances

No toxicological data available for the substances.

11.1.2. Mixture

Skin corrosion/skin irritation :

Corrosive classification is based on an extreme pH value.

Serious damage to eyes/eye irritation :

Corrosive classification is based on an extreme pH value.

SECTION 12 : ECOLOGICAL INFORMATION

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

.1. Substances	
SODIUM HYPOCHLORITE, SOLUTION% C Fish toxicity :	L ACTIVE (CAS: 7681-52-9) 0.01 < LC50 <= 0.1 mg/l Factor M = 10 Duration of exposure : 96 h
	0,01 < NOEC <= 0,1 mg/l Duration of exposure : 28 days
Crustacean toxicity :	0.01 < EC50 <= 0.1 mg/l Factor M = 10 Species : Ceriodaphnia sp. Duration of exposure : 48 h
	0,001 < NOEC <= 0,01 mg/l Factor M = 1 Duration of exposure : 7 days
Algae toxicity :	$0.01 < \text{ECr50} \le 0.1 \text{ mg/l}$ Factor M = 10 Duration of exposure : 72 h
	0,001 < NOEC <= 0,01 mg/l Factor M = 1 Duration of exposure : 7 days

12.1.2. Mixtures

Crustacean toxicity :

Toxic. 1 < EC50 <= 10 mg/l Species : Daphnia magna Duration of exposure : 24 h

Other guideline

12.2. Persistence and degradability

12.2.1. Substances

SODIUM HYPOCHLORITE, SOLUTION ...% CL ACTIVE (CAS: 7681-52-9) Biodegradability : Rapidly degradable.

12.2.2. Mixtures

no degradability data is available, the substance is considered as not degrading quickly.

Biodegradability :

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container. Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2013 - IMDG 2012 - ICAO/IATA 2014).

14.1. UN number

1791

14.2. UN proper shipping name

UN1791=HYPOCHLORITE SOLUTION

14.3. Transport hazard class(es)

- Classification :



8

14.4. Packing group

III

14.5. Environmental hazards

- Environmentally hazardous material :



14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	8	C9	III	8	80	5 L	521	E1	3	E
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ			
	8	-	III	5 L	F-A,S-B	223	E1			
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	8	-	III	852	5 L	856	60 L	A3	E1	
								A803		
	8	-	III	Y841	1 L	-	-	A3	E1	7
								A803		

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 67/548/EEC and its adaptations
- Directive 1999/45/EC and its adaptations
- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.

- Container information:

Packaging to be fitted with child-resistant fastenings (see EC Regulation No. 1272/2008, Annex II, Part 3).

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Hazard symbols :



Corrosive



Dangerous for the environment

ıt.
).

S 26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S 29	Do not empty into drains.
S 36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
S 45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
S 25	Avoid contact with eyes.
S 27	Take off immediately all contaminated clothing.
S 28	After contact with skin, wash immediately with plenty of (to be specified by the manufacturer).
S 64	If swallowed, rinse mouth with water (only if the person is conscious).
S 20	When using do not eat or drink.
Title for H, EUH and R	indications mentioned in section 3 :
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH031	Contact with acids liberates toxic gas.
R 22	Harmful if swallowed.
R 31	Contact with acids liberates toxic gas.
R 34	Causes burns.
R 35	Causes severe burns.
R 37	Irritating to respiratory system.
R 38	Irritating to skin.
R 41	Risk of serious damage to eyes.
R 50	Very toxic to aquatic organisms.
R 52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS05 : Corrosion

GHS09 : Environment