

SAFETY DATA SHEET ODOUR NEUTRALIZER - CRANBERRY

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME ODOUR NEUTRALIZER - CRANBERRY

PART NUMBER 865417 / 865424

APPLICATION AIR FRESHENER

SUPPLIER QUEST CONSUMABLES LIMITED

STOCK HOUSE SEYMOUR ROAD NUNEATON WARWICKSHIRE

CV11 4LB

TELEPHONE +44 (0)24 76 322126 FACSIMILE +44 (0)24 76 322117

E MAIL info@questconsumables.com

SECTION 2: HAZARDS IDENTIFICATION

CLASSIFICATION (1995/45) F+;R12.

HUMAN HEALTH

Gas or vapour is harmful on prolonged exposure or in high concentrations. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

ENVIRONMENT

This product does not contain substances which are harmful to aquatic organisms or which may cause long term effects to the aquatic environment

PHYSICAL AND CHEMICAL HAZARDS

Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable, and explosive vapour/air mixtures may be formed even at normal room temperatures. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

LABEL ELEMENTS

LABELLING



Extremely flammable

SAFETY PHRASES	R12	Extremely flammable.			
	A1	Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.			
	A2	Do not spray on a naked flame or any incandescent material.			
	S2	Keep out of the reach of children.			
	S16	Keep away from sources of ignition - No smoking.			
	S23	Do not breathe vapour/spray.			
	S51	Use only in well-ventilated areas.			
	P14	Contains Methyl Esters of Rosin (Partially Hydrogenated). May produce an allergic reaction.			

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

MIXTURES

BUTANE 30-60%

CAS-No.: 106-97-8 EC No.: 203-448-7

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Gas 1 - H220 F+;R12

Hexyl Salicylate <1

CAS-No.: 6259-76-3 EC No.: 228-408-6

Classification (EC 1272/2008) Classification (67/548/EEC)

Skin Irrit. 2 - H315 Xi;R38. Aquatic Acute 1 - H400 N;R50/53. Aquatic Chronic 1 - H410

ISOBUTANE 10-30%

CAS-No.: 75-28-5 EC No.: 200-857-2

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Gas 1 - H220 F+;R12

Methyl Esters of Rosin (Partially Hydrogenated)

CAS-No.: 8050-15-5 EC No.: 232-476-2

Classification (EC 1272/2008) Classification (67/548/EEC)

Not classified. R43.

PROPAN-2-OL 10-30%

CAS-No.: 67-63-0 EC No.: 200-661-7

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Liq. 2 - H225 F;R11
Eye Irrit. 2 - H319 Xi;R36
STOT SE 3 - H336 R67

PROPANE 10-30%

CAS-No.: 74-98-6 EC No.: 200-827-9

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Gas 1 - H220 F+;R12

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

GENERAL INFORMATION

Move the exposed person to fresh air at once.

INHALATION

In case of inhalation of spray mist: Move person into fresh air and keep at rest. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

Immediately rinse mouth and provide fresh air. Do not induce vomiting. Get medical attention.

SKIN CONTACT

Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above.

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

SECTION 5: FIREFIGHTING MEASURES

EXTINGUISHING MEDIA

Extinguish with foam, carbon dioxide, dry powder or water fog.

SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

UNUSUAL FIRE & EXPLOSION HAZARDS

Extremely flammable. Forms explosive mixtures with air. May travel considerable distance to source of ignition and flash back. Aerosol cans may explode in a fire.

SPECIFIC HAZARDS

Aerosol containers can explode when heated, due to excessive pressure build-up.

ADVICE FOR FIREFIGHTERS

SPECIAL FIRE FIGHTING PROCEDURES

Water spray should be used to cool containers. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT & EMEGENCY PROCEDURES

Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Avoid inhalation of vapours and aerosol spray.

ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses. Contain spillages with sand, earth or any suitable adsorbent material.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb spillage with non-combustible, absorbent material. Let evaporate. Keep out of confined spaces because of explosion risk.

REFERENCE TO OTHER SECTIONS

SECTION 7: HANDLING AND STORAGE

PRECUATIONS FOR SAFE HANDLING

Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Do not spray near a naked flame or any incandescent material.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY IMCOMPATIBILITIES

Extremely flammable. Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

SPECIFIC END USE(S)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CONTROL PARAMETERS

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
BUTANE	WEL	600 ppm		750 ppm		
ISOBUTANE	WEL	800 ppm		No std.		
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

EXPOSURE CONTROLS

ENGINEERING MEASURES

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of spray.

RESPIRATORY EQUIPMENT

In case of inadequate ventilation use suitable respirator.

HAND PROTECTION

Due to the packaging form, aerosol, risk of skin contact is small. For prolonged or repeated skin contact use suitable protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

HYGIENE MEASURES

Wash hands after handling. Wash promptly if skin becomes contaminated. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin.

PERSONAL PROTECTION

When using do not smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance Aerosol.

Odour Fruity.

Flash point (°C) <-40 °C

Auto Ignition Temperature (°C) 410-580

Flammability Limit - Lower(%) 1.8

Flammability Limit - Upper(%) 9.5

Comments Information given concerns the major ingredient.

9.2. Other information

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY

CHEMICAL STABILITY

Avoid Heat, sparks, flames.

POSSIBILITY OF HAZARDOUS REACTIONS

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

INCOMPLETE MATERIALS

HAZARDOUS DECOMPOSITION PRODUCTS

In case of fire, toxic gases (CO, CO2, NOx) may be formed.

SECTION 11: TOXICOLOGICAL INFORMATION

INFORMATION ON TOXOLOGICAL EFFECTS

General information

Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

Inhalation

In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Unconsciousness, possibly death.

Skin contact

Skin irritation is not anticipated when used normally. Repeated exposure may cause skin dryness or cracking.

Eye contact

Spray and vapour in the eyes may cause irritation and smarting.

Health Warnings

Arrhythmia, (deviation from normal heart beat). In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Route of entry

Inhalation.

Target Organs

Central nervous system Respiratory system, lungs

Medical Symptoms

Arrhythmia, (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

No negative effects on the aquatic environment are known. The product is not expected to be toxic to aquatic organisms.

TOXICITY

PERSISTENCE AND DEGRADABILITY

BIOACCUMULATIVE POTENTIAL

MOBILITY IN SOIL

RESULTS OF PBT AND vPvB ASSESSMENT

OTHER ADVERSE EFFECTS

SECTION 13: DISPOSAL CONSIDERATIONS

General information

Do not puncture or incinerate even when empty.

WASTE TREATMENT METHODS

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk). Empty containers must not be burned because of explosion hazard.

SECTION 14: TRANSPORT INFORMATION

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and

IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities.

Aerosols not so packed and labelled must show the following.

UN NUMBER

 UN No. (ADR/RID/ADN)
 1950

 UN No. (IMDG)
 1950

 UN No. (ICAO)
 1950

UN PROPER SHIPPING NAME

Proper Shipping Name AEROSOLS

TRANSPORT HAZARD CLASS(ES)

ADR/RID/ADN Class 2, 5F

ADR/RID/ADN Class Class 2.1: Flammable gases.

ADR Label No. 3

IMDG Class 2.1

ICAO Class/Division 2.1

Transport Labels



PACKING GROUP

ADR/RID/ADN Packing group Not Applicable

IMDG Packing group Not Applicable

ICAO Packing group Not Applicable

ENVIRONMENTAL HAZARDS

SPECIAL PRECAUTIONS FOR USER

EMS 2-13

Hazard No. (ADR) 23 Flammable gas.

Tunnel Restriction Code (D)

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL73/78 AND THE IBC CODE

SECTION 15: REGULATORY INFORMATION

SAFETY, HEALTH & ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

Uk Regulatory References

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. Chemicals (Hazard Information & Packaging) Regulations.

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health. The Aerosol Dispensers Regulations 1977 & 1999

Approved Code Of Practice

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply. British Aerosol Manufacturers Code of Practice 7th. Edition 1999

Guidance Notes

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

EU Legislation

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC.

National Regulations

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689.

CHEMICAL SAFETY ASSESSMENT

SECTION 16: OTHER INFORMATION

SDS No. 11915
Safety Data Sheet Status Approved.
Date 16.04.2013

Risk Phrases In Full

R12 Extremely flammable.
R11 Highly flammable
R36 Irritating to eyes.
R38 Irritating to skin.

R43 May cause sensitisation by skin contact.
R67 Vapours may cause drowsiness and dizziness.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Hazard Statements In Full

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H222 Extremely flammable aerosol. H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

H400 Very toxic to aquatic life.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.