



MORRIS
LUBRICANTS

Product Information:

LIQUIMATIC SUPER ATF AUTOMATIC TRANSMISSION OIL

Description

Liquimatic Super ATF is an automatic transmission fluid blended from high quality mineral oil and a balanced additive system. This grade has superior performance in terms of frictional characteristics, seal compatibility, oxidation stability, low temperature fluidity and resistance to high temperatures encountered during severe operating conditions.

Applications

Liquimatic Super ATF is recommended for use in a range of applications, where a product of this quality is specified. Applications include: automatic transmissions, powershift transmissions, transaxles, torque converters, hydrostatic drives, fluid couplings, fluid clutches, transfer boxes, brake boosters, levelling systems, hydraulic systems, bogie lifts, cab tilt mechanisms, motorcycle suspension forks, etc.

DO NOT USE in automotive transmissions specifying Ford ESW-M2C33-F fluids (see Liquimatic 33G).

Performance Levels

Allison TES-389B / TES-228 (C-4)
ATF LT71141 / 7045E / 3403-M115
BMW ETL-8072B / LA2634 / ZF 5HP18L,
Chrysler ATF+ / +2 / +3 (MS 7176E)
Ford Mercon® / ESP-M2C138-CJ / I66-H / XT-2-QDX/M / XL-12
Ford XT-2-QDX / XT-2-QSM
GM Dexron® II / IID / IIE / IIIG / IIHH / TASA
GM 1940700 / 21005966
Hyundai – Kia Dex-II / SP-11
Jaquar JLM 20238 / M115 / JLM 20292
Jeep ATF+3
Maxda ATF D-II / M-III / F-I
NAG I
Opel/GM 19 40 700 / 19 40 767 / 21005966 Transaxle / 22 17266
Porsche 000 043 205 09 / 999 917 547 00 (A2) / Z 000169756
Peugeot-Citroen Z 000169756 / AL4 Auto Gearbox Oil (#9730.AE)
Renault DPO/AL4 / Matic D2
Toyota ATFD-II / ATF D-III
Volvo 97325 / 97335 / CE 97340
VW G-052 169 / US 000 162
ZF TE-ML 05L / 09 / 21L / Lifeguard 5
ZF all 3 and 4 speed
ZF 5HP 18FL / 19FL / 24A / 30

Physical Characteristics

Appearance	Red
Density at 15.6 °C	0.858
Viscosity @ 100 °C, cSt.	7.1
Viscosity @ 40 °C, cSt.	35.9
Viscosity Index	167
Flash Point (Closed) °C	195
Pour Point, °C	-51

Figures based on average production values.

Part No.S: ATF001, ATF005, ATF025, ATF205

(TDS Liquimatic Super ATF – 051120 Issue 17)

