

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier Product name Ring Free XHD 10W Product number 7421 Internal identification GHS21568 **REACH** registration number n/a Mixture 1.2. Relevant identified uses of the substance or mixture and uses advised against Identified uses Lubricant. Uses advised against Non specified unless otherwise stated within this MSDS 1.3. Details of the supplier of the safety data sheet Supplier Morris Lubricants **Castle Foregate** Shrewsbury SY1 2EL 08.45 - 17.00 GMT T: (+44)(0)1743 232200 F: (+44)(0)1743 353584 sds@morris-lubricants.co.uk 1.4. Emergency telephone number **Emergency telephone** +44 (0)1743 232200 (08.45 - 17.00 hrs GMT) **SECTION 2: Hazards identification** 2.1. Classification of the substance or mixture Classification Physical hazards Not Classified Health hazards Elicitation - EUH208 **Environmental hazards** Not Classified Classification (67/548/EEC or Not Classified 1999/45/EC) 2.2. Label elements Hazard statements EUH208 Contains Calcium long chain alkaryl sulphonate, Calcium long chain alkaryl sulphonate. May produce an allergic reaction. Supplemental label EUH210 Safety data sheet available on request. information

Contains	Distillates (petroleum), solvent-dewaxed heavy	paraffinic
----------	--	------------

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures			
Distillates (petroleum), solve	nt-dewaxed heavy paraffinic		60-100%
CAS number: 64742-65-0	EC number: 265-16		EACH registration number: 01- 119471299-27-XXXX
Classification Asp. Tox. 1 - H304		Classification (67/548/ -	EEC or 1999/45/EC)
Polyolefin polyamine succinin CAS number: —	mide polyol		1-5%
Classification Aquatic Chronic 4 - H413		Classification (67/548/ R53.	EEC or 1999/45/EC)
Propylene Pentamer CAS number: 15220-87-8			<1%
Classification Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		Classification (67/548 / Xn;R65. Xi;R38. N;R5	•
The Full Text for all R-Phrase	s and Hazard Statements are Dis	played in Section 16.	
Composition comments	If REACH registration numbers registration, does not meet the volume threshold for registratio information is proprietary.	minimum	
SECTION 4: First aid measure	es		
4.1. Description of first aid me	asures		
General information	Get medical attention if any dis	comfort continues.	
Inhalation			ve affected person to fresh air and eathing. Get medical attention if any
Ingestion	Get medical attention if any dis	comfort continues. Do	not induce vomiting.
Skin contact	Remove contaminated clothing	immediately and wash	skin with soap and water.
Eye contact			ontact lenses and open eyelids wide edical attention promptly if symptoms
4.2. Most important symptoms	s and effects, both acute and dela	lyed	
• • • •	1 6 1 (1 1 1 1 1 1 1 1		

Inhalation	Upper respiratory irritation.	
Ingestion	May cause discomfort if swallowed. The product contains mineral oil, which if aspirated into the lungs through vomitting after ingestion, may result in chemical pneumonia.	
Skin contact	Prolonged contact may cause redness, irritation and dry skin.	
Eye contact	Irritation of eyes and mucous membranes.	
4.3. Indication of any immedia	te medical attention and special treatment needed	
Notes for the doctor	Treat symptomatically.	
SECTION 5: Firefighting meas	sures	
5.1. Extinguishing media		
Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.	
Unsuitable extinguishing	Do not use water jet as an extinguisher, as this will spread the fire.	
media		
5.2. Special hazards arising fro		
Specific hazards	Heat from fire could result in drums bursting	
Hazardous combustion products	Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.	
5.3. Advice for firefighters		
Protective actions during firefighting	Control run-off water by containing and keeping it out of sewers and watercourses.	
Special protective equipment for firefighters	Wear self-contained breathing apparatus.	
SECTION 6: Accidental releas	e measures	
6.1. Personal precautions, pro	tective equipment and emergency procedures	
Personal precautions	For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.	
6.2. Environmental precaution	S	
Environmental precautions	Contain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.	
6.3. Methods and material for containment and cleaning up		
Methods for cleaning up	Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment	
6.4. Reference to other section	ns	
Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.	
SECTION 7: Handling and sto	r070	

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	Avoid spilling. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets.
7.2. Conditions for safe storage	e, including any incompatibilities
Storage precautions	Store in tightly-closed, original container in a dry, cool and well-ventilated place.
Storage class	Miscellaneous hazardous material storage.
7.3. Specific end use(s)	
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
SECTION 8: Exposure Control	ols/personal protection
8.1. Control parameters	
Occupational exposure limits	
Distillates (petroleum), solven	t-dewaxed heavy paraffinic
Long-term exposure limit (8-h Short-term exposure limit (15-	, -
Propylene Pentamer	
Long-term exposure limit (8-h	our TWA): WEL 4 mg/m ³
ACGIH = American Conference WEL = Workplace Exposure L	ce of Governmental Industrial Hygienists. .imit
	Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS: 64742-65-0)
DNEL	- Inhalation; : 5.4 mg/m ³
PNEC	- ; 9.33 mg/kg
8.2. Exposure controls	
Protective equipment	
Appropriate engineering controls	Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.
Hand protection	The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.
Other skin and body protection	Use barrier creams to prevent skin contact.
Hygiene measures	Use engineering controls to reduce air contamination to permissible exposure level. Wash

Respiratory protection No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

Thermal hazards	Not anticipated under normal conditions of use. The product is combustible if heated excessively and an ignition source is applied.
Environmental exposure controls	Do not allow product to contaminate land.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Amber.
Odour	Characteristic. Oil-like.
Odour threshold	Not known.
рН	Not applicable.
Melting point	-39°C Pour point
Initial boiling point and range	>320°C @ 101.3 kPa
Flash point	200°C PMCC (Pensky-Martens closed cup).
Evaporation rate	Not relevant.
Upper/lower flammability or explosive limits	Not known.
Other flammability	Product is not flammable but on excessive heating may become combustible.
Vapour pressure	<0.1 kPa @ 20°C
Vapour density	Not determined.
Relative density	0.882 @ 15.6°C
Solubility(ies)	Insoluble in water. Soluble in the following materials: Organic solvents.
Partition coefficient	Not determined. log Kow: > 7 The above figure is typical of mineral oil.
Auto-ignition temperature	No specific test data are available.
Decomposition Temperature	Not determined.
Viscosity	33.9 cSt @ 40°C
Explosive properties	Not considered to be explosive.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.
9.2. Other information	
Volatile organic compound	The product is a complex mixture, the majority of which would not be classed as a VOC. However it cannot be discounted that trace or low levels of VOC's may be present.
SECTION 10: Stability and rea	activity
10.1. Reactivity	
Reactivity	There are no known reactivity hazards associated with this product.
10.2. Chemical stability	

Stability	Stable at normal ambient temperatures and when used as recommended.	
10.3. Possibility of hazardous r	eactions	
Possibility of hazardous reactions	Unlikely to occur under normal conditions of use. Unlikely to occur.	
10.4. Conditions to avoid		
Conditions to avoid	Avoid heat, flames and other sources of ignition.	
10.5. Incompatible materials		
Materials to avoid	Strong oxidising agents.	
10.6. Hazardous decomposition	n products	
Hazardous decomposition products	Oxides of carbon. Oxides of nitrogen.	
SECTION 11: Toxicological info	ormation	
11.1. Information on toxicologic	cal effects	
Acute toxicity - oral		
Notes (oral LD∞)	Not expected to be highly toxic based on information of ingredients. Based on available data the classification criteria are not met.	
Acute toxicity - dermal		
Notes (dermal LD₅₀)	Not expected to be highly toxic based on information of ingredients. Based on available data the classification criteria are not met.	
Acute toxicity - inhalation		
Notes (inhalation LC₅₀)	Not determined. The product is unlikely to present any significant inhalation hazard at ambient temperatures and under normal conditions of use.	
Serious eye damage/irritation		
Serious eye damage/irritation	May cause mild, short lasting discomfort to eyes.	
Respiratory sensitisation		
Respiratory sensitisation	No evidence to suggest the product will be a respiratory sensitiser. Repeated exposure to oil mists may cause respiratory damage.	
Skin sensitisation		
Skin sensitisation	Not expected to be a skin sensitizer based on information on components.	
Carcinogenicity		
Carcinogenicity	This product contains mineral oils which are considered to be severly refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP346 test	
Reproductive toxicity		
Reproductive toxicity - fertility	No data available to suggest the product will cause reproductive toxicity.	
Specific target organ toxicity - single exposure		
STOT - single exposure	Based on available data the classification criteria are not met.	
Specific target organ toxicity - r	repeated exposure	
STOT - repeated exposure	Based on available data the classification criteria are not met.	
Aspiration hazard		

Aspiration hazard	Kinematic viscosity > 20.5 mm ² /s. The product viscosity is greater than the upper limit assigned for classification. The product contains mineral oil. If aspirated into the lungs e.g. through vomitting after ingestion admit to hospital immediately.
General information	This product has low toxicity. Only large quantities are likely to have adverse effects on human health.
Inhalation	Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature.
Ingestion	No harmful effects expected from quantities likely to be ingested by accident.
Skin contact	Skin irritation should not occur when used as recommended. Repeated exposure may cause skin dryness or cracking.
Eye contact	May cause temporary eye irritation.
Acute and chronic health hazards	Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis and skin cancer.

SECTION 12: Ecological Infor	mation	
Ecotoxicity	Based on available data the classification criteria are not met. Not regarded as dangerous for the environment.	
12.1. Toxicity		
Toxicity	Based on available data the classification criteria are not met. Not considered toxic to fish.	
Acute toxicity - aquatic invertebrates	Based on available data the classification criteria are not met.	
12.2. Persistence and degrad	ability	
Persistence and degradability	The product contains mineral oil which has limited biodegradability in CEC test methods but will biodegrade slowly in aerobic water and sediments and is considered ultimately biodegradable.	
Stability (hydrolysis)	The product is based on highly refined mineral oils that are considered stable to hydrolysis.	
Biodegradation	The product is not considered readily biodegradeable, albeit the major constituents are expected to ultimately biodegrade.	
Biological oxygen demand	Not determined.	
Chemical oxygen demand	Not determined.	
12.3. Bioaccumulative potenti	al	
Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.	
Partition coefficient	Not determined. log Kow: > 7 The above figure is typical of mineral oil.	
12.4. Mobility in soil		
Mobility	The product is non-volatile. The product is insoluble in water and will spread on the water surface.	
Henry's law constant	Not determined.	
12.5. Results of PBT and vPv	B assessment	
Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.	
12.6. Other adverse effects		
Other adverse effects	None known.	
SECTION 13: Disposal considerations		
13.1. Waste treatment method	ds	
General information	This material and its container must be disposed of as hazardous waste. Dispose of waste via a licensed waste disposal contractor.	
Disposal methods	Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Dispose of waste via a licensed waste disposal contractor.	
Waste class	European waste catalogue (EWC) number = 13 02 08* (other engine, gear and lubricating oil)	
SECTION 14: Transport information		
General	The product is not covered by international regulations on the transport of dangerous goods	

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture		
National regulations	Health and Safety at Work etc. Act 1974 (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009	
	No. 716).	
	Control of Substances Hazardous to Health Regulations 2002 (as amended).	
	The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment	
	Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].	
EU legislation	Dangerous Preparations Directive 1999/45/EC.	
	Dangerous Substances Directive 67/548/EEC.	
	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18	
	December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of	
	Chemicals (REACH) (as amended).	
	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16	
	December 2008 on classification, labelling and packaging of substances and mixtures (as amended).	
Guidance	Workplace Exposure Limits EH40.	
	Safety Data Sheets for Substances and Preparations.	

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

Inventories

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

Australia - AICS

All the ingredients are listed or exempt.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines – PICCS All the ingredients are listed or exempt.

New Zealand - NZIOC

All the ingredients are listed or exempt.

SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	19/11/2015
Revision	1
SDS number	21568
Hazard statements in full	EUH208 Contains Calcium long chain alkaryl sulphonate, Calcium long chain alkaryl sulphonate. May produce an allergic reaction. H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.