

# Product Information: ULTRALIFE RED ORGANIC ACID TECHNOLOGY ANTIFREEZE

### **Description**:

Ultralife Red will protect all engines from frost damage right down to  $-40^{\circ}$ C. It also provides outstanding protection against rust and corrosion for all parts of the cooling system and is therefore recommended for all year round use. This Ethylene Glycol based antifreeze, which uses Organic Acid Technology, is free from nitrites, amines, phosphates, borates and silicates. When used at the correct concentration, coolants based on Organic Acid Technology are capable of providing extended operation compared to conventional antifreeze. This can be for up to 5 years or 250,000km in passenger cars and 500,000km in commercial vehicles, depending which is reached first.

# Applications

Ultralife Red is suitable for the cooling systems of modern engines in cars, vans, trucks and contractors plant, where an OAT antifreeze is recommended.

## Performance

Meets the requirements of the following International Standards: ASTM D3306 ASTM D 4985 SAE J 1034 BS 6580 (2010) AFNOR NF R15-601 \* FFV Heft R443 CUNA NC 956-16 UNE 26361 - 88 JIS K 2234 \* NATO S 759

(\* with the exception of reserve alkalinity)

Meets the performance requirements of the following OEM specifications: Chrysler MS 9176

Chrysler MS 9176 Cummins CES 14603 Ford ESE M97B49-A, WSS-M97B44-D &ESD M97 B49-A GM 1899 M, US 6277 M & OPEL GM OL130100 John Deere H 24 B1 & C1 Leyland Trucks LTS 22 AF 10 Mack 014GS 17004 MAN 248, 324 (SNF) & B&W D 36 5600 Mercedes MB 325.3, Renault 41-01-001 - D VAG TL 774 D/F/G, VW G12+ VOLVO VCS STD 418-0001 Scania TB 1451 DAF 74002

Solution % Vol.	Freezing Point °C	SG Reading
25	-12	1.040
33	-22	1.055
40	-27	1.073
50	-40	1.086

#### **Physical Characteristcs**

Clear red/orange liquid		
1.125		
174		
8.0		
3.0		
7.5		

Figures based on average production values.

Part No.s ULR005, ULR025, ULR205



www.morrislubricants.co.uk

(TDS Ultra Life Red - 081216 Issue 7)