

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product name	Versimax HD6 15W-40
Product number	7403
Internal identification	GHS21559
REACH registration number	n/a Mixture
1.2. Relevant identified uses of	of the substance or mixture and uses advised against
Identified uses	Engine oil.
Uses advised against	Non specified unless otherwise stated within this MSDS
1.3. Details of the supplier of t	he safety data sheet
Supplier	Morris Lubricants Castle Foregate Shrewsbury
	SY1 2EL
	08.45 - 17.00 GMT
	T: (+44)(0)1743 232200
	F: (+44)(0)1743 353584
	sds@morris-lubricants.co.uk
1.4. Emergency telephone nu	mber
Emergency telephone	+44(0)1743 232200 (08.45 - 17.00 GMT)
SECTION 2: Hazards identific	ation
2.1. Classification of the subst	ance or mixture
Classification	
Physical hazards	Not Classified
Health hazards	Elicitation - EUH208
Environmental hazards	Not Classified
Classification (67/548/EEC or 1999/45/EC)	Not Classified
2.2. Label elements Hazard statements	EUH208 Contains Calcium long chain alkaryl sulphonate. May produce an allergic reaction.

# Precautionary statements P264 Wash contaminated skin thoroughly after handling. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention. P501a Dispose of contents/container to hazardous or special waste collection point.

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

### SECTION 3: Composition/information on ingredients 3.2. Mixtures Distillates, hydrotreated heavy paraffinic 60-100% CAS number: 64742-54-7 EC number: 265-157-1 **REACH** registration number: 01-2119484627-25-0014 Classification Classification (67/548/EEC or 1999/45/EC) Not Classified 5-10% Lubricating oil (petroleum) C20-C50, hydrotreated, neutral oilbased CAS number: 72623-87-1 EC number: 276-738-4 REACH registration number: 01-2119474889-13-XXXX Classification Classification (67/548/EEC or 1999/45/EC) Not Classified Distillates, hydrotreated heavy paraffinic 5-10% CAS number: 64742-54-7 EC number: 265-157-1 REACH registration number: 01-2119484627-25-0014 Classification Classification (67/548/EEC or 1999/45/EC) Asp. Tox. 1 - H304 Polyolefin polyamine succinimide borated 1-5% CAS number: ---Classification Classification (67/548/EEC or 1999/45/EC) Aquatic Chronic 4 - H413 R53. Polyolefin polyamine succinimide 1-5% CAS number: ----Classification Classification (67/548/EEC or 1999/45/EC) Aquatic Chronic 4 - H413 R53.

Phosphorodithioic acid, O,C	o-di-C1-14-alkyl esters, zinc salts		1-5%
CAS number: 68649-42-3	EC number: 272-02	8-3 REACH registration number: 01- 2119657973-23-XXXX	
Classification		Classification (67/548/EEC or 1999/45/EC)	
Skin Irrit. 2 - H315		Xi;R41. N;R51/53.	
Eye Dam. 1 - H318			
Aquatic Chronic 2 - H411			
Polyolefin polyamine succin	imide polyol		1-5%
CAS number: —			
Classification		Classification (67/548/EEC or 1999/45/EC)	
Aquatic Chronic 4 - H413		R53.	
Propylene Pentamer			<19
CAS number: 15220-87-8			
Classification		Classification (67/548/EEC or 1999/45/EC)	
Asp. Tox. 1 - H304		Xn;R65. Xi;R38. N;R51/53.	
Aquatic Chronic 2 - H411			
The Full Text for all R-Phrase	es and Hazard Statements are Dis	played in Section 16.	
Composition comments	If REACH registration numbers	do not appear the substance is either exempt from	
	registration, does not meet the		
	information is proprietary.	on, the registration date has not yet come due or this	
SECTION 4: First aid measu	res		
I.1. Description of first aid m	easures		
General information	Get medical attention if any dis	comfort continues. May produce an allergic reaction.	
nhalation		proceed as follows. Move affected person to fresh air an ition comfortable for breathing. Get medical attention if a	
ngestion	Get medical attention if any dis	comfort continues. Do not induce vomiting.	
Skin contact	Remove contaminated clothing	immediately and wash skin with soap and water.	
Eye contact		of water. Remove any contact lenses and open eyelids w east 15 minutes. Get medical attention promptly if sympto	
.2. Most important symptom	ns and effects, both acute and dela	ayed	
General information	If aspiration into the lungs is su	spected, eg when vomitting, admit to hospital immediate	ly.
nhalation	Upper respiratory irritation.		
ngestion	May cause discomfort if swallo	wed. The product contains mineral oil, which if aspirated	into

IngestionMay cause discomfort if swallowed. The product contains mineral oil, which if aspirated into<br/>the lungs through vomitting after ingestion, may result in chemical pneumonia.

Skin contact Prolonged contact may cause redness, irritation and dry skin.

Eye contact	Irritation of eyes and mucous membranes.	
4.3. Indication of any immediate medical attention and special treatment needed		
Notes for the doctor	Treat symptomatically.	
SECTION 5: Firefighting meas	jures	
5.1. Extinguishing media		
Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
5.2. Special hazards arising from	om the substance or mixture	
Specific hazards	Heat from fire could result in drums bursting	
Hazardous combustion products	Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen. Fire may also create other unidentified organic gases some of which may be toxic.	
5.3. Advice for firefighters		
Protective actions during firefighting	Control run-off water by containing and keeping it out of sewers and watercourses.	
Special protective equipment for firefighters	Wear self-contained breathing apparatus.	
SECTION 6: Accidental release	e measures	
6.1. Personal precautions, pro	tective equipment and emergency procedures	
Personal precautions	For personal protection, see Section 8. In case of spills, beware of slippery floors and surfaces.	
6.2. Environmental precaution	S	
Environmental precautions	Contain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or watercourses. The product is insoluble in water and will spread on the water surface.	
6.3. Methods and material for	containment and cleaning up	
Methods for cleaning up	Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. In case of spillage on water prevent the spread by use of suitable barrier equipment	
6.4. Reference to other section	6.4. Reference to other sections	
Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.	
SECTION 7: Handling and storage		
7.1. Precautions for safe hand	ling	
Usage precautions	Avoid spilling. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags	

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly-closed, original container in a dry, cool and well-ventilated place.

moistened with oil into pockets.

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

### SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

Occupational exposure limits

### Distillates, hydrotreated heavy paraffinic

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m<sup>3</sup> Short-term exposure limit (15-minute): ACGIH 10 mg/m<sup>3</sup>

### Lubricating oil (petroleum) C20-C50, hydrotreated, neutral oil-based

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m<sup>3</sup>

### **Propylene Pentamer**

Long-term exposure limit (8-hour TWA): WEL 4 mg/m<sup>3</sup>

ACGIH = American Conference of Governmental Industrial Hygienists.

WEL = Workplace Exposure Limit

### Lubricating oil (petroleum) C20-C50, hydrotreated, neutral oil- based (CAS: 72623-87-1)

### Ingredient comments

Finnish HTP 5mg/m3 8 hr

### 8.2. Exposure controls

### Protective equipment

Appropriate engineering controls	Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.
Hand protection	The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.
Other skin and body protection	Use barrier creams to prevent skin contact.
Hygiene measures	Use engineering controls to reduce air contamination to permissible exposure level. Wash promptly with soap and water if skin becomes contaminated.
Respiratory protection	No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.
Thermal hazards	Not anticipated under normal conditions of use. The product is combustible if heated excessively and an ignition source is applied.
Environmental exposure controls	Do not allow product to contaminate land.

**SECTION 9: Physical and Chemical Properties** 

# 9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Amber.
Odour	Characteristic. Oil-like.
Odour threshold	Not known.
рН	Not applicable.
Melting point	-34°C Pour point
Initial boiling point and range	>320°C @ 101.3 kPa
Flash point	208°C PMCC (Pensky-Martens closed cup).
Evaporation rate	Not relevant.
Upper/lower flammability or explosive limits	Not known.
Other flammability	Product is not flammable but on excessive heating may become combustible.
Vapour pressure	<0.1 kPa @ 20°C
Vapour density	Not determined.
Relative density	0.877 @ 15.6°C
Solubility(ies)	Insoluble in water. Soluble in the following materials: Organic solvents.
Partition coefficient	Not determined. log Kow: > 7 This figure is typical of mineral oil.
Auto-ignition temperature	No specific test data are available.
Decomposition Temperature	Not determined.
Viscosity	104.7 cSt @ 40°C
Explosive properties	Not considered to be explosive.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.
9.2. Other information	
Volatile organic compound	The product is a complex mixture, the majority of which would not be classed as a VOC. However it cannot be discounted that trace or low levels of VOC's may be present.
SECTION 10: Stability and rea	activity
10.1. Reactivity	
Reactivity	There are no known reactivity hazards associated with this product.
10.2. Chemical stability	
Stability	Stable at normal ambient temperatures and when used as recommended.
10.3. Possibility of hazardous	reactions
Possibility of hazardous reactions	Unlikely to occur under normal conditions of use. Unlikely to occur.

10.4. Conditions to avoid	
Conditions to avoid	Avoid heat, flames and other sources of ignition.
10.5. Incompatible materials	
Materials to avoid	Strong oxidising agents.
10.6. Hazardous decompositio	n products
Hazardous decomposition products	Oxides of carbon. Oxides of nitrogen.
SECTION 11: Toxicological inf	ormation
11.1. Information on toxicologic	cal effects
Acute toxicity - oral	
Notes (oral LD∞)	Not expected to be highly toxic based on information of ingredients. Based on available data the classification criteria are not met.
Acute toxicity - dermal	
Notes (dermal LD₅₀)	Not expected to be highly toxic based on information of ingredients. Based on available data the classification criteria are not met.
Acute toxicity - inhalation	
Notes (inhalation LC₅₀)	Not determined. The product is unlikely to present any significant inhalation hazard at ambient temperatures and under normal conditions of use.
Serious eye damage/irritation	
Serious eye damage/irritation	May cause mild, short lasting discomfort to eyes.
Respiratory sensitisation	
Respiratory sensitisation	No evidence to suggest the product will be a respiratory sensitiser. Repeated exposure to oil mists may cause respiratory damage.
Skin sensitisation	
Skin sensitisation	Not expected to be a skin sensitizer based on information on components.
Carcinogenicity	
Carcinogenicity	This product contains mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP346 test
Reproductive toxicity	
Reproductive toxicity - fertility	No data available to suggest the product will cause reproductive toxicity.
Specific target organ toxicity -	single exposure
STOT - single exposure	Based on available data the classification criteria are not met.
Specific target organ toxicity - I	repeated exposure
STOT - repeated exposure	Based on available data the classification criteria are not met.
Aspiration hazard	
Aspiration hazard	Kinematic viscosity > 20.5 mm <sup>2</sup> /s. The product viscosity is greater than the upper limit assigned for classification. Although not classified, the product contains mineral oil. If aspirated into the lungs e.g. through vomiting after ingestion, admit to hospital immediately.
General information	This product has low toxicity. Only large quantities are likely to have adverse effects on human health.

Inhalation	Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature.
Ingestion	No harmful effects expected from quantities likely to be ingested by accident.
Skin contact	Skin irritation should not occur when used as recommended. Repeated exposure may cause skin dryness or cracking.
Eye contact	May cause temporary eye irritation.
Acute and chronic health hazards	Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis and skin cancer.

SECTION 12: Ecological Information	
Ecotoxicity	Based on available data the classification criteria are not met. Not regarded as dangerous for the environment.
12.1. Toxicity	
Toxicity	Based on available data the classification criteria are not met. Not considered toxic to fish.
Acute toxicity - aquatic invertebrates	Based on available data the classification criteria are not met.
12.2. Persistence and degrada	bility
Persistence and degradability	The product contains mineral oil which has limited biodegradability in CEC test methods but will biodegrade slowly in aerobic water and sediments and is considered ultimately biodegradable.
Stability (hydrolysis)	The product is based on highly refined mineral oils that are considered stable to hydrolysis.
Biodegradation	The product is not considered readily biodegradeable, albeit the major constituents are expected to ultimately biodegrade.
Biological oxygen demand	Not determined.
Chemical oxygen demand	Not determined.
12.3. Bioaccumulative potentia	
Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.
Partition coefficient	Not determined. log Kow: > 7 This figure is typical of mineral oil.
12.4. Mobility in soil	
Mobility	The product is non-volatile. The product is insoluble in water and will spread on the water surface.
Henry's law constant	Not determined.
12.5. Results of PBT and vPvE	3 assessment
Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.
12.6. Other adverse effects	
Other adverse effects	None known.
SECTION 13: Disposal conside	erations
13.1. Waste treatment method	S
General information	This material and its container must be disposed of as hazardous waste. Dispose of waste via a licensed waste disposal contractor.
Disposal methods	Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Dispose of waste via a licensed waste disposal contractor.
Waste class	European waste catalogue (EWC) number = 13 02 05* (mineral based non-chlorinated engine, gear & lubricating oils)
SECTION 14: Transport inform	nation

### 9/11

### General

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

### 14.1. UN number

Not applicable.

### 14.2. UN proper shipping name

Not applicable.

### 14.3. Transport hazard class(es)

No transport warning sign required.

### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

### 14.6. Special precautions for user

Not applicable.

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

### Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	<ul> <li>Health and Safety at Work etc. Act 1974 (as amended).</li> <li>The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).</li> <li>Control of Substances Hazardous to Health Regulations 2002 (as amended).</li> <li>The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].</li> </ul>
EU legislation	Dangerous Preparations Directive 1999/45/EC. Dangerous Substances Directive 67/548/EEC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40. Safety Data Sheets for Substances and Preparations.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### Inventories

### Canada - DSL/NDSL

All the ingredients are listed or exempt.

### US - TSCA

All the ingredients are listed or exempt.

### Australia - AICS

All the ingredients are listed or exempt.

Korea - KECI All the ingredients are listed or exempt.

China - IECSC All the ingredients are listed or exempt.

Philippines – PICCS All the ingredients are listed or exempt.

### New Zealand - NZIOC

All the ingredients are listed or exempt.

### **SECTION 16: Other information**

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Issued by	Regulatory Affairs
Revision date	26/11/2015
Revision	6
Supersedes date	14/10/2015
SDS number	21559
Hazard statements in full	<ul> <li>EUH208 Contains Calcium long chain alkaryl sulphonate. May produce an allergic reaction.</li> <li>H304 May be fatal if swallowed and enters airways.</li> <li>H315 Causes skin irritation.</li> <li>H318 Causes serious eye damage.</li> <li>H411 Toxic to aquatic life with long lasting effects.</li> <li>H413 May cause long lasting harmful effects to aquatic life.</li> </ul>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.