



Product Information:

## **VERSIMAX HD6 15W-40**

### **LOW EMISSION MULTIGRADE DIESEL ENGINE OIL**

#### **Description**

Versimax HD6 15W-40 is a mid-SAPS heavy duty diesel engine oil, manufactured from Group II base fluids. This product contains an advanced additive package formulated to provide the utmost protection when operating in very severe conditions with extended drain intervals.

Versimax HD6 15W-40 has been developed for use in diesel engines fitted with exhaust gas re-circulation (EGR), selective catalytic reduction (SCR – Adblue) NOx reduction systems, diesel oxidation catalysts (DOC) and diesel particulate filters (DPF).

#### **Applications**

Versimax HD6 15W-40 is designed for use in Euro 5 / Euro 6, Interim Tier 4 / Stage 3B / Tier 4 and Stage 4 diesel engines, where any of the performance levels shown below are specified. Market sectors include: commercial vehicles, coaches, buses, off-highway and agricultural equipment, etc. Manufacturers include: Caterpillar, Cummins, DDC, Mack, MB, MAN, Renault, Volvo.

#### **Performance Levels**

API CJ-4 / SM

ACEA E7 / E9

CAT ECF-2 / ECF-3

Cummins CES 20076

Cummins CES 20081 (Approved)

MAN M3575

Mack EO-O Premium Plus Approval

Detroit Diesel DFS Oil Specification 93K218 (Conformance)

Mercedes Benz 228.31

Volvo VDS-4 Approval (417-0001-09-204)

Renault VI RLD-3 Compliance

Deutz DQC III-10 LA Approved

MTU Type 2.1

Scania LA

Versimax HD6 15W-40 has demonstrated performance against JASO DH-1 and 2.

#### **Physical Characteristics**

Density @ 15°C	0.870
Kinematic Viscosity at 100°C, cSt.	14.85
Kinematic Viscosity at 40°C, cSt.	107.42
Viscosity Index	143
Flash Point (closed) °C	210
TBN, mg/KOH/g	9.34
Pour Point, °C	-33

Figures based on average production values.

Part No.s: UPL025, UPL205

(TDS Versimax HD6 15W-40– 160117 Issue 4)

