Revision 2

Supersedes date 15/4/11



SAFETY DATA SHEET Swarfega Duck Oil

According to Regulation (EU) No 453/2010

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product nameSwarfega Duck OilProduct No.SDO25L, SDO5L

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Lubricant. Car maintenance product. Releasing agent. . For full details regarding recommended uses

please refer to the product label.

1.3. Details of the supplier of the safety data sheet

Supplier Deb Ltd

Denby Hall Way

Denby Derbyshire DE5 8JZ

Main Tel. 01773 855100 Technical Tel 01773 855105

reach@deb.co.uk

1.4. Emergency telephone number

National Poisons Information Service (UK) 0844 8920111

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (1999/45/EEC) Xn;R65. R66.

Environment

The product does not meet the requirement for classification as an environmental hazard in accordance with directive 1999/45/EEC

2.2. Label elements

Contains DISTILLATES PETROLEUM HYDROCARBON LIGHT

Labelling



Harmful

Risk Phrases

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

Safety Phrases

S2 Keep out of the reach of children.

S62 If swallowed, do not induce vomiting: seek medical advice immediately and

show this container or label.

S35 This material and its container must be disposed of in a safe way.

S51 Use only in well-ventilated areas.

2.3. Other hazards

Not Classified as PBT/vPvB by current EU criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

DISTILLATES PETROLEUM HYDROCARBON LIGHT			60-100%
CAS-No.: 64742-47-8	EC No.: 926-141-6		Registration Number: 01-2119456620-43
Classification (EC 1272/2008)		Classification (67/548/EEC)	
EUH066 Asp. Tox. 1 - H304		Xn;R65. R66.	

FATTY ALCOHOL POLYGLYCOL ETHER 2-5 EO				
CAS-No.:	EC No.:			
Classification (EC 1272/2008)		Classification (67/548/EEC)		
Eye Dam. 1 - H318		Xi;R41.		
Aquatic Chronic 2 - H411		N;R51/53.		

ISO-BUTANOL

CAS-No.: 78-83-1 EC No.: 201-148-0

Classification (EC 1272/2008)	Classification (67/548/EEC)
Flam. Liq. 3 - H226	R10
Skin Irrit. 2 - H315	Xi;R37/38,R41
Eye Dam. 1 - H318	R67
STOT SE 3 - H335	
STOT SE 3 - H336	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation

Remove victim immediately from source of exposure. Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

Ingestion

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention immediately!

Skin contact

Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.

Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation

Nausea, vomiting. Vapours may cause drowsiness and dizziness. Upper respiratory irritation.

Ingestion

Diarrhoea. Fumes from the stomach contents may be inhaled resulting in the same symptoms as inhalation. Nausea, vomiting.

Skin contact

Prolonged contact may cause redness, irritation and dry skin.

Eye contact

Irritating and may cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

No specific first aid measures noted.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

During fire, toxic gases (CO, CO2) are formed.

5.3. Advice for firefighters

Special Fire Fighting Procedures

No specific fire fighting procedure given.

Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Do not discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

6.4. Reference to other sections

For personal protection, see section 8.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact. Provide good ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA	- 8 Hrs	STEL ·	- 15 Min	Notes
ISO-BUTANOL	WEL	50 ppm	154 mg/m3	75 ppm	231 mg/m3	

WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment





Engineering measures

Must not be handled in confined space without sufficient ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

Hand protection

Use protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Use protective gloves made of: SPECIFIC RECOMMENDATIONS. Nitrile. Polyvinyl alcohol (PVA). Viton rubber (fluor rubber).

Eye protection

Wear approved safety goggles.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

AppearanceLiquidColourBrown.

OdourCharacteristic.SolubilityInsoluble in water

Initial boiling point and boiling range (°C)

Not determined.

Melting point (°C)

Not determined.

Relative density

Not determined.

Vapour density (air=1)

Not determined.

Vapour pressure

Not determined.

Evaporation rate

Not determined.

pH-Value, Conc. Solution

Scientifically unjustified.

Viscosity

Not determined.

Decomposition temperature (°C)

Not determined.

Odour Threshold, Lower

Not determined.

Odour Threshold, Upper

Not determined.

Flash point (°C) 70 deg C

Auto Ignition Temperature (°C)

Not determined.

Flammability Limit - Lower(%)

Not determined.

Flammability Limit - Upper(%)

Not determined

Partition Coefficient

(N-Octanol/Water)

Not determined.

Explosive properties

Not determined.

Solid: Burning time. Not applicable

Oxidising properties

Does not meet the criteria for oxidising

9.2. Other information

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No specific reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

Not relevant

Hazardous Polymerisation

Unknown.

10.4. Conditions to avoid

There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials To Avoid

No incompatible groups noted.

10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity:

Acute Toxicity (Oral LD50)

No information available.

Acute Toxicity (Dermal LD50)

No information available.

Acute Toxicity (Inhalation LC50)

Not determined.

Skin Corrosion/Irritation:

Based on available data the classification criteria are not met.

Respiratory or skin sensitisation:

Based on available data the classification criteria are not met.

Germ cell mutagenicity:

Based on available data the classification criteria are not met.

Carcinogenicity:

Does not contain any substances known to be carcinogenic.

Reproductive Toxicity:

Does not contain any substances known to be toxic to reproduction.

Specific target organ toxicity - single exposure:

STOT - Single exposure

No information available

Specific target organ toxicity - repeated exposure:

STOT - Repeated exposure

No information available.

Inhalation

Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion

Harmful: may cause lung damage if swallowed. Nausea, vomiting. Diarrhoea.

Skin contact

Prolonged contact may cause dryness of the skin.

Eye contact

May cause temporary eye irritation.

Toxicological information on ingredients.

DISTILLATES PETROLEUM HYDROCARBON LIGHT (CAS: 64742-47-8)

Acute toxicity:

Acute Toxicity (Oral LD50)

> 5000 mg/kg

Acute Toxicity (Dermal LD50)

> 5000 mg/kg

Acute Toxicity (Inhalation LC50)

> 5000 mg/l (vapours)

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Not regarded as dangerous for the environment.

12.1. Toxicity

The product does not meet the requirement for classification as an environmental hazard in accordance with directive 1999/45/EEC

 LC 50, 96 Hrs, Fish mg/l
 >1000

 EC 50, 48 Hrs, Daphnia, mg/l
 >1000

 IC 50, 72 Hrs, Algae, mg/l
 >1000

Not known.

Ecological information on ingredients.

DISTILLATES PETROLEUM HYDROCARBON LIGHT (CAS: 64742-47-8)

LC 50, 96 Hrs, Fish mg/l

>1000

EC 50, 48 Hrs, Daphnia, mg/l

>1000

IC 50, 72 Hrs, Algae, mg/l

>1000

21 days 1.22 mg/l Daphnia magna

12.2. Persistence and degradability

Degradability

There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

Partition coefficient

Not determined.

12.4. Mobility in soil

Mobility:

The product is insoluble in water and will spread on the water surface.

12.5. Results of PBT and vPvB assessment

Not Classified as PBT/vPvB by current EU criteria.

12.6. Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

General information

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority.

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Do not allow runoff to sewer, waterway or ground. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 14: TRANSPORT INFORMATION

General The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA,

ADR/RID).

Road Transport NotesNot ClassifiedRail Transport NotesNot classified.Sea Transport NotesNot classified.Air Transport NotesNot classified.

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

Not applicable.

Transport Labels

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Legislation

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Commission Directive 91/322/EEC of 29 May 1991 on establishing indicative limit values by implementing Council Directive 80/1107/EEC on the protection of workers from the risks related to exposure to chemical, physical and biological agents at work. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work. System of specific information relating to Dangerous Preparations. 2001/58/EC.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

General information

Only trained personnel should use this material.

Revision Comments

New REACH Annex 2 Compliant MSDS

Revision Date 30/09/2011

Revision 2 Supersedes date 25/4/11

Risk Phrases In Full

R10 Flammable.

R65 Harmful: may cause lung damage if swallowed.

R37/38 Irritating to respiratory system and skin.

R66 Repeated exposure may cause skin dryness or cracking.

R41 Risk of serious damage to eyes.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

Hazard Statements In Full

EUH066 Repeated exposure may cause skin dryness or cracking.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Notes for Risk Phrases and Hazard Statements in Full

The full text for Risk Phrases and Hazard Statements in section 16 relates to the reference numbers in sections 2 and 3 and not necessarily the finished product classification.