



SAFETY DATA SHEET

FIXT Dry Lube + PTFE

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name FIXT Dry Lube + PTFE
 Product No. FX081325

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Dry lubricant spray

1.3. Details of the supplier of the safety data sheet

Supplier Quest Consumables Ltd
 Stock House
 Seymour Road
 Nuneaton
 Warwickshire
 CV11 4LB

TELEPHONE +44 (0)24 76 322126
 FACSIMILE +44 (0)24 76 322117
 E MAIL info@fixtconsumables.com
 EMERGENCY TELEPHONE NUMBER +44 (0)24 76 322196

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (1999/45/EEC) Xi;R38. F+;R12. R52/53, R67.

Human health

Gas or vapour is harmful on prolonged exposure or in high concentrations. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

Environment

This product contains substances which are very toxic or toxic to aquatic organisms and may cause long term effects to the aquatic environment (see sections 2 and 12)

Physical and Chemical Hazards

Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable, and explosive vapour/air mixtures may be formed even at normal room temperatures. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

2.2. Label elements

Labelling



Irritant



Extremely flammable

Risk Phrases

| | |
|--------|---|
| R12 | Extremely flammable. |
| R38 | Irritating to skin. |
| R52/53 | Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R67 | Vapours may cause drowsiness and dizziness. |

Safety Phrases

| | |
|--------|---|
| A1 | Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. |
| A2 | Do not spray on a naked flame or any incandescent material. |
| S2 | Keep out of the reach of children. |
| S16 | Keep away from sources of ignition - No smoking. |
| S23 | Do not breathe vapour/spray. |
| S24 | Avoid contact with skin. |
| S29/56 | Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. |
| S51 | Use only in well-ventilated areas. |

2.3. Other hazards

FIXT Dry Lube + PTFE

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

| | |
|--|--|
| BUTANE | 10-30% |
| CAS-No.: 106-97-8 | EC No.: 203-448-7 |
| Classification (EC 1272/2008) Flam. Gas 1 - H220 | Classification (67/548/EEC) F+;R12 |
| BUTANOL-norm | < 1 |
| CAS-No.: 71-36-3 | EC No.: 200-751-6 |
| Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT Single 3 - H335 STOT Single 3 - H336 | Classification (67/548/EEC) R10 Xn;R22 Xi;R37/38,R41 R67 |
| ISOBUTANE | 10-30% |
| CAS-No.: 75-28-5 | EC No.: 200-857-2 |
| Classification (EC 1272/2008) Flam. Gas 1 - H220 | Classification (67/548/EEC) F+;R12 |
| Naphtha (petroleum) hydrodesulfurized light dearomatized | 10-30% |
| CAS-No.: 92045-53-9 | EC No.: 295-434-2 |
| Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT Single 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411 | Classification (67/548/EEC) Xn;R65. Xi;R38. F;R11. N;R51/53. R67. |
| Naphtha (petroleum) hydrotreated light | 10-30% |
| CAS-No.: 64742-49-0 | EC No.: 265-151-9 |
| Classification (EC 1272/2008) Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT Single 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411 | Classification (67/548/EEC) Xn;R65. Xi;R38. F;R11. N;R51/53. R67. |
| PROPAN-2-OL | 5-10% |
| CAS-No.: 67-63-0 | EC No.: 200-661-7 |
| Classification (EC 1272/2008) Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT Single 3 - H336 | Classification (67/548/EEC) F;R11 Xi;R36 R67 |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

FIXT Dry Lube + PTFE

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

Move the exposed person to fresh air at once.

Inhalation

In case of inhalation of spray mist: Move person into fresh air and keep at rest. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

Immediately rinse mouth and provide fresh air. Do not induce vomiting. Get medical attention.

Skin contact

Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above.

Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Extinguish with foam, carbon dioxide, dry powder or water fog.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Extremely flammable. Forms explosive mixtures with air. May travel considerable distance to source of ignition and flash back. Aerosol cans may explode in a fire.

Specific hazards

Aerosol containers can explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Water spray should be used to cool containers. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Avoid inhalation of vapours and aerosol spray.

6.2. Environmental precautions

Do not allow to enter drains, sewers or watercourses. Contain spillages with sand, earth or any suitable adsorbent material.

6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb spillage with non-combustible, absorbent material. Let evaporate. Keep out of confined spaces because of explosion risk.

6.4. Reference to other sections

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Do not spray near a naked flame or any incandescent material.

7.2. Conditions for safe storage, including any incompatibilities

Extremely flammable. Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

7.3. Specific end use(s)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

FIXT Dry Lube + PTFE

| Name | STD | TWA - 8 Hrs | | STEL - 15 Min | | Notes |
|--|-----|-------------|------------|---------------|---------------|-------|
| | | | | | | |
| BUTANE | WEL | 600 ppm | | 750 ppm | | |
| BUTANOL-norm | WEL | | | 50 ppm(Sk) | 154 mg/m3(Sk) | |
| ISOBUTANE | WEL | 800 ppm | | No std. | | |
| Naphtha (petroleum) hydrodesulfurized light dearomatized | | 315 ppm | 1200 mg/m3 | | | |
| Naphtha (petroleum) hydrotreated light | | 315 ppm | 1200 mg/m3 | | | |
| PROPAN-2-OL | WEL | 400 ppm | 999 mg/m3 | 500 ppm | 1250 mg/m3 | |

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Engineering measures

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of spray.

Respiratory equipment

In case of inadequate ventilation use suitable respirator.

Hand protection

Due to the packaging form, aerosol, risk of skin contact is small. Use suitable protective gloves if risk of skin contact. Gloves of nitrile rubber, PVA or Viton are recommended. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable.

Hygiene measures

Wash hands after handling. Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate hand lotion to prevent defatting and cracking of skin.

Personal protection

When using do not smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

| | |
|--------------------------------|--|
| Appearance | Aerosol. |
| Odour | Organic solvents. |
| Flash point (°C) | <-40 °C |
| Auto Ignition Temperature (°C) | 410-580 |
| Flammability Limit - Lower(%) | 1.8 |
| Flammability Limit - Upper(%) | 9.5 |
| Comments | Information given concerns the major ingredient. |

9.2. Other information

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

10.2. Chemical stability

Avoid Heat, sparks, flames.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

10.5. Incompatible materials

10.6. Hazardous decomposition products

In case of fire, toxic gases (CO, CO₂, NO_x) may be formed.

SECTION 11: TOXICOLOGICAL INFORMATION

FIXT Dry Lube + PTFE

11.1. Information on toxicological effects

General information

Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

Inhalation

In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Unconsciousness, possibly death.

Skin contact

Irritating to skin.

Eye contact

Spray and vapour in the eyes may cause irritation and smarting.

Health Warnings

Arrhythmia, (deviation from normal heart beat). Irritating to skin. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Route of entry

Inhalation.

Target Organs

Central nervous system Respiratory system, lungs

Medical Symptoms

Skin irritation. Arrhythmia, (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

This product has not been tested but contains ingredients which are toxic or very toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment. During normal use the volatility of the components and the packaging form, pressurised container, make entry into the aquatic environment unlikely, however, do not empty or discharge into drains or watercourses. Ensure container is empty before disposal to prevent contents entering watercourses.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: DISPOSAL CONSIDERATIONS

General information

Do not puncture or incinerate even when empty.

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk). Empty containers must not be burned because of explosion hazard.

SECTION 14: TRANSPORT INFORMATION

General

This product is packed in accordance with the Limited Quantity Provisions of CDG CPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following.

14.1. UN number

| | |
|----------------------|------|
| UN No. (ADR/RID/ADN) | 1950 |
| UN No. (IMDG) | 1950 |
| UN No. (ICAO) | 1950 |

14.2. UN proper shipping name

| | |
|----------------------|----------|
| Proper Shipping Name | AEROSOLS |
|----------------------|----------|

14.3. Transport hazard class(es)

| | |
|-------------------|-----------------------------|
| ADR/RID/ADN Class | 2, 5F |
| ADR/RID/ADN Class | Class 2.1: Flammable gases. |

FIXT Dry Lube + PTFE

| | |
|---------------------|-----|
| ADR Label No. | 3 |
| IMDG Class | 2.1 |
| ICAO Class/Division | 2.1 |
| Transport Labels | |

**14.4. Packing group**

| | |
|---------------------------|----------------|
| ADR/RID/ADN Packing group | Not Applicable |
| IMDG Packing group | Not Applicable |
| ICAO Packing group | Not Applicable |

14.5. Environmental hazards**14.6. Special precautions for user**

| | |
|------------------|-------------------|
| EMS | 2-13 |
| Hazard No. (ADR) | 23 Flammable gas. |

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**SECTION 15: REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Uk Regulatory References**

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. Chemicals (Hazard Information & Packaging) Regulations.

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health. The Aerosol Dispensers Regulations 1977 & 1999

Approved Code Of Practice

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply. British Aerosol Manufacturers Code of Practice 7th. Edition 1999

Guidance Notes

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

EU Legislation

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC.

National Regulations

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689.

15.2. Chemical Safety Assessment**SECTION 16: OTHER INFORMATION**

| | |
|--------------------------|------------|
| SDS No. | 12420 |
| Safety Data Sheet Status | Approved. |
| Date | 24.10.2011 |

FIXT Dry Lube + PTFE**Risk Phrases In Full**

| | |
|--------|---|
| R12 | Extremely flammable. |
| R10 | Flammable. |
| R22 | Harmful if swallowed. |
| R65 | Harmful: may cause lung damage if swallowed. |
| R11 | Highly flammable |
| R36 | Irritating to eyes. |
| R37/38 | Irritating to respiratory system and skin. |
| R38 | Irritating to skin. |
| R41 | Risk of serious damage to eyes. |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R67 | Vapours may cause drowsiness and dizziness. |

Hazard Statements In Full

| | |
|------|--|
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H220 | Extremely flammable gas. |
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H225 | Highly flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H336 | May cause drowsiness or dizziness. |
| H335 | May cause respiratory irritation. |
| H411 | Toxic to aquatic life with long lasting effects. |

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.