

Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 11

Loctite 248

sds no. : 153639 V003.0 Revision: 26.01.2011 printing date: 01.05.2012

1. Identification of the substance/mixture and of the company/undertaking

Product identifier: Loctite 248 Relevant identified uses of the substance or mixture and uses advised against: Intended use: Anaerobic

Details of the supplier of the safety data sheet:

Henkel Limited 2 Bishop Square Business Park AL109EY Herfordshire Hatfield

Great Britain

Phone: +44 1606 593933 Fax-no.: +44 1606 863762

 $ua\-products a fety.uk@uk.henkel.com$

Emergency telephone number:

24 Hours Emergency Tel: +44 (0)1442 278497

2. Hazards identification

Classification of the substance or mixture: Classification (DPD):

Xi - Irritant R36/37 Irritating to eyes and respiratory system.

Label elements (DPD):

Xi - Irritant



Risk phrases: R36/37 Irritating to eyes and respiratory system.

Safety phrases:

S25 Avoid contact with eyes.S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.S51 Use only in well-ventilated areas.

Additional labeling:

For consumer use only: S2 Keep out of the reach of children S46 If swallowed, seek medical advice immediately and show this container or label.

Other hazards:

None if used properly.

3. Composition/information on ingredients

General chemical description:

Methacrylate resin based threadlocker

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Ethane-1,2-diol 107-21-1	203-473-3	> 1-< 3%	Acute toxicity 4; Oral H302
Cumene hydroperoxide 80-15-9	201-254-7	> 1-< 2,5 %	Acute toxicity 4; Dermal H312 Specific target organ toxicity - repeated exposure 2 H373 Acute toxicity 3; Inhalation H331 Acute toxicity 4; Oral H302 Organic peroxides E H242 Chronic hazards to the aquatic environment 2 H411 Skin corrosion 1B H314
1-Methyl-2-pyrrolidone 872-50-4	212-828-1	> 0,1-< 0,5 %	Toxic to reproduction 1B H360D Serious eye irritation 2 H319 Specific target organ toxicity - single exposure 3 H335 Skin irritation 2 H315
Cumene 98-82-8	202-704-5	> 0,1-< 0,5 %	Flammable liquids 3 H226 Aspiration hazard 1 H304 Specific target organ toxicity - single exposure 3 H335 Chronic hazards to the aquatic environment 2 H411

Only dangerous ingredients for which a CLP classification is already available are displayed in this table. For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Ethane-1,2-diol 107-21-1	203-473-3	> 1-< 3 %	Xn - Harmful; R22
Cumene hydroperoxide 80-15-9	201-254-7	> 1-< 2,5 %	T - Toxic; R23 Xn - Harmful; R21/22, R48/20/22 O - Oxidizing; R7 C - Corrosive; R34 N - Dangerous for the environment; R51, R53
1-Methyl-2-pyrrolidone 872-50-4	212-828-1	> 0,1 - < 0,5 %	Toxic for reproduction - category 2.; R61 Xi - Irritant; R36/37/38
Cumene 98-82-8	202-704-5	> 0,1 - < 0,5 %	R10 Xn - Harmful; R65 Xi - Irritant; R37 N - Dangerous for the environment; R51, R53

For full text of the R-Phrases indicated by codes see section 16 'Other Information'. Substances without classification may have community workplace exposure limits available.

4. First aid measures

Description of first aid measures:

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap. Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting. Seek medical advice.

Most important symptoms and effects, both acute and delayed:

EYE: Irritation, conjunctivitis.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

Indication of any immediate medical attention and special treatment needed:

See section: Description of first aid measures

5. Firefighting measures

Extinguishing media:

Suitable extinguishing media: Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

Special hazards arising from the substance or mixture:

Trace amounts of toxic and/or irritating fumes may be released and the use of breathing apparatus is recommended.

Advice for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Avoid skin and eye contact.

Environmental precautions:

Waste disposal with the approval of the responsible local authority.

Reference to other sections:

See advice in chapter 8

7. Handling and storage

Precautions for safe handling:

Use only in well-ventilated areas. Avoid skin and eye contact. Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Hygiene measures:

Good industrial hygiene practices should be observed. Do not eat, drink or smoke while working. Wash hands before work breaks and after finishing work.

Conditions for safe storage, including any incompatibilities:

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

Specific end use(s): Anaerobic

8. Exposure controls/personal protection

Control parameters: Valid for

Great Britain

Ingredient	ppm mg/m ³ Type Category		Category	Remarks	
ETHYLENE GLYCOL			Skin designation:	Can be absorbed through the	ECTLV
107-21-1			-	skin.	
ETHANE-1,2-DIOL, VAPOUR	40	104	Short Term Exposure		EH40 WEL
107-21-1			Limit (STEL):		
ETHANE-1,2-DIOL, PARTICULATE			Skin designation:	Can be absorbed through the	EH40 WEL
107-21-1				skin.	
ETHANE-1,2-DIOL, VAPOUR			Skin designation:	Can be absorbed through the	EH40 WEL
107-21-1			-	skin.	
ETHANE-1,2-DIOL, PARTICULATE		10	Time Weighted Average		EH40 WEL
107-21-1			(TWA):		
ETHANE-1,2-DIOL, VAPOUR	20	52	Time Weighted Average		EH40 WEL
107-21-1			(TWA):		
ETHYLENE GLYCOL	20	52	Time Weighted Average	Indicative	ECTLV
107-21-1			(TWA):		
ETHYLENE GLYCOL	40	104	Short Term Exposure	Indicative	ECTLV
107-21-1			Limit (STEL):		
1-METHYL-2-PYRROLIDONE	75	309	Short Term Exposure		EH40 WEL
872-50-4			Limit (STEL):		
1-METHYL-2-PYRROLIDONE			Skin designation:	Can be absorbed through the	EH40 WEL
872-50-4			-	skin.	
1-METHYL-2-PYRROLIDONE	25	103	Time Weighted Average		EH40 WEL
872-50-4			(TWA):		
N-METHYL-2-PYRROLIDONE	10	40	Time Weighted Average	Indicative	ECTLV
872-50-4			(TWA):		
N-METHYL-2-PYRROLIDONE	20	80	Short Term Exposure	Indicative	ECTLV
872-50-4			Limit (STEL):		
N-METHYL-2-PYRROLIDONE			Skin designation:	Can be absorbed through the	ECTLV
872-50-4				skin.	
CUMENE	25	125	Time Weighted Average		EH40 WEL
98-82-8			(TWA):		
CUMENE	50	250	Short Term Exposure		EH40 WEL
98-82-8			Limit (STEL):		
CUMENE			Skin designation:	Can be absorbed through the	EH40 WEL
98-82-8				skin.	
CUMENE			Skin designation:	Can be absorbed through the	ECTLV
98-82-8				skin.	
CUMENE	50	250	Short Term Exposure	Indicative	ECTLV
98-82-8			Limit (STEL):		
CUMENE	20	100	Time Weighted Average	Indicative	ECTLV
98-82-8			(TWA):		

Exposure controls:

Respiratory protection: Use only in well-ventilated areas.

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

9. Physical and chemical properties

...

Information on basic physical and chemical proper	rties:
Appearance	solid
	blue
Odor	characteristic
pH	not applicable
Initial boiling point	> 150,0 °C (> 302 °F)
Flash point	>100 °C (>212 °F)
Decomposition temperature	No data available / Not applicable
Vapour pressure	< 6,66 mbar
(25,0 °C (77 °F))	
Density	1,1000 g/cm3
0	
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Solubility (qualitative)	Slight
(Solvent: Water)	0
Solubility (qualitative)	Not determined
(Solvent: Acetone)	
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

Other information:

No data available / Not applicable

10. Stability and reactivity

Reactivity:

Strong oxidizing agents. Free radical initiators.

Possibility of hazardous reactions: See section reactivity

Conditions to avoid:

Stable under normal conditions of storage and use.

Incompatible materials:

None if used properly.

Hazardous decomposition products:

Oxides of carbon.

11. Toxicological information

General toxicological information:

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

May cause irritation to the digestive tract.

Inhalative toxicity:

Irritating to respiratory system

Skin irritation:

Although it is not a common sensitizer there may be a risk of sensitization on prolonged or repeated contact with damaged skin

Eye irritation:

Irritating to eyes.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Ethane-1,2-diol 107-21-1	LD50	> 2.000 mg/kg	oral		rat	EU Method B.1 (Acute Toxicity (Oral))
1-Methyl-2-pyrrolidone 872-50-4	LD50 LC50	5.010 mg/kg > 5,1 mg/l	oral inhalation	4 h	rat rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
1-Methyl-2-pyrrolidone 872-50-4	slightly irritating		rabbit	
1-Methyl-2-pyrrolidone 872-50-4	moderately irritating		human	

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
1-Methyl-2-pyrrolidone 872-50-4	not irritating		rabbit	

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Ethane-1,2-diol 107-21-1	negative	bacterial forward mutation assay	with and without		

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
1-Methyl-2-pyrrolidone 872-50-4	NOAEL=0,5 mg/l	inhalation	90 days 6 hrs/day, 5 days/wk	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

12. Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

In the cured state contribution of this product to Environmental Hazards is insignificant in comparison to articles in which it is used.

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Ecotoxicity:

No data available for the product.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Ethane-1,2-diol 107-21-1	LC50	72.860 mg/l	Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute
	NOEC	15.380 mg/l	Fish	28 d	Oryzias latipes	Toxicity Test) OECD Guideline 204 (Fish,
Ethane-1,2-diol 107-21-1	EC50	34.400 mg/l	Daphnia	48 h	Ceriodaphnia sp.	Prolonged Toxicity Test: 14-day Study) OECD Guideline 202 (Daphnia sp. Acute Immobilisation
Ethane-1,2-diol 107-21-1	EC50	> 20.000 mg/l	Algae		Microcystis aeruginosa	Test) OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute
Cumene hydroperoxide 80-15-9	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	Toxicity Test) OECD Guideline 202 (Daphnia sp. Acute Immobilisation
Cumene hydroperoxide 80-15-9	ErC50	3,1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	Test) OECD Guideline 201 (Alga, Growth
1-Methyl-2-pyrrolidone 872-50-4	LC50	4.000 mg/l	Fish	96 h	Leuciscus idus	Inhibition Test)
1-Methyl-2-pyrrolidone 872-50-4	EC50	4.897 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation
1-Methyl-2-pyrrolidone 872-50-4	EC50	> 500 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	Test)
Cumene 98-82-8	LC50	4,8 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene 98-82-8	EC50	4 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation
Cumene 98-82-8	EC50	2,6 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)	Test) OECD Guideline 201 (Alga, Growth Inhibition Test)

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Ethane-1,2-diol 107-21-1	readily biodegradable	aerobic	83 - 96 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
Cumene hydroperoxide 80-15-9			18 %	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
1-Methyl-2-pyrrolidone 872-50-4		aerobic	99 %	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
Cumene 98-82-8		aerobic	86 %	

Bioaccumulative potential / Mobility in soil:

Hazardous components	LogKow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			

Ethane-1,2-diol 107-21-1	-1,36				
Cumene hydroperoxide 80-15-9		9,1			OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
Cumene hydroperoxide 80-15-9	2,16				
1-Methyl-2-pyrrolidone 872-50-4	-0,11				
Cumene 98-82-8		35,5	Carassius auratus		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
Cumene 98-82-8	3,55			23 °C	OECD Guideline 107 (Partition Coefficient (n- octanol / water), Shake Flask Method)

13. Disposal considerations

Waste treatment methods:

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

14. Transport information

General information:

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

VOC content (1999/13/EC) < 3 %

16. Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R10 Flammable.

R21/22 Harmful in contact with skin and if swallowed.

R22 Harmful if swallowed.

R23 Toxic by inhalation.

R34 Causes burns.

R36/37/38 Irritating to eyes, respiratory system and skin.

R37 Irritating to respiratory system.

R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R51 Toxic to aquatic organisms.

R53 May cause long-term adverse effects in the aquatic environment.

R61 May cause harm to the unborn child.

R65 Harmful: may cause lung damage if swallowed.

R7 May cause fire.

H226Flammable liquid and vapour. H242Heating may cause a fire. H302Harmful if swallowed. H304May be fatal if swallowed and enters airways. H312Harmful in contact with skin. H314Causes severe skin burns and eye damage. H315Causes skin irritation. H319Causes serious eye irritation. H331Toxic if inhaled. H335May cause respiratory irritation. H360DMay damage the unborn child. H373May cause damage to organs through prolonged or repeated exposure. H411Toxic to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and it's subsequent amendments, and Commission Directive 1999/45/EC.