

# SAFETY DATA SHEET FIXT Multipurpose Clear Fine Oil

#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name FIXT Multipurpose Clear Fine Oil

Product No. FX081330

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Lubricant aerosol

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** Seymour Road

Nuneaton Warwickshire CV11 4LB

TELEPHONE +44 (0)24 76 322126 FACSIMILE +44 (0)24 76 322117

E MAIL info@fixtconsumables.com
EMERGENCY TELEPHONE NUMBER +44 (0)24 76 322196

#### **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

Classification (1999/45/EEC) F+;R12. R52/53.

**Environment** 

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

#### 2.2. Label elements

# Labelling



Extremely flammable

Risk Phrases

R12 Extremely flammable.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Safety Phrases

A1 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

A2 Do not spray on a naked flame or any incandescent material.

S2 Keep out of the reach of children.

S16 Keep away from sources of ignition - No smoking.

S23 Do not breathe vapour/spray.

S29/56 Do not empty into drains, dispose of this material and its container at

hazardous or special waste collection point.

Use only in well-ventilated areas.

#### 2.3. Other hazards

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.2. Mixtures

# **FIXT Multipurpose Clear Fine Oil**

BUTANE

CAS-No.: 106-97-8

EC No.: 203-448-7

Classification (EC 1272/2008)

Classification (67/548/EEC)

F+:R12

ISOBUTANE 5-10%

CAS-No.: 75-28-5 EC No.: 200-857-2

Flam. Gas 1 - H220

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Gas 1 - H220 F+;R12

OCTANE 10-30%

CAS-No.: 111-65-9 EC No.: 203-892-1

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Liq. 2 - H225 F;R11
Skin Irrit. 2 - H315 Xn;R65
STOT SE 3 - H336 Xi;R38
Asp. Tox. 1 - H304 R67
Aquatic Acute 1 - H400 N;R50/53
Aquatic Chronic 1 - H410

PROPANE 10-30%

CAS-No.: 74-98-6 EC No.: 200-827-9

Classification (EC 1272/2008) Classification (67/548/EEC)

Flam. Gas 1 - H220 F+;R12

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

# **SECTION 4: FIRST AID MEASURES**

# 4.1. Description of first aid measures

#### **General information**

Move the exposed person to fresh air at once.

# Inhalation

In case of inhalation of spray mist: Move person into fresh air and keep at rest. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

#### Ingestion

Immediately rinse mouth and provide fresh air. DO NOT induce vomiting. Get medical attention immediately.

# Skin contact

Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above.

#### Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.3. Indication of any immediate medical attention and special treatment needed

#### **SECTION 5: FIREFIGHTING MEASURES**

### FIXT Multipurpose Clear Fine Oil

### 5.1. Extinguishing media

#### **Extinguishing media**

Extinguish with foam, carbon dioxide, dry powder or water fog.

#### 5.2. Special hazards arising from the substance or mixture

#### **Unusual Fire & Explosion Hazards**

Extremely flammable. Forms explosive mixtures with air. May travel considerable distance to source of ignition and flash back. Aerosol cans may explode in a fire.

#### Specific hazards

Aerosol containers can explode when heated, due to excessive pressure build-up.

# 5.3. Advice for firefighters

#### Special Fire Fighting Procedures

Water spray should be used to cool containers. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Avoid inhalation of vapours and aerosol spray.

#### 6.2. Environmental precautions

Do not allow to enter drains, sewers or watercourses. Contain spillages with sand, earth or any suitable adsorbent material.

#### 6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb spillage with non-combustible, absorbent material. Let evaporate. Keep out of confined spaces because of explosion risk.

#### 6.4. Reference to other sections

# **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Do not spray near a naked flame or any incandescent material.

#### 7.2. Conditions for safe storage, including any incompatibilities

Extremely flammable. Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 degrees Centigrade. Do not pierce or burn, even after use.

#### Storage Class

Flammable compressed gas storage.

#### 7.3. Specific end use(s)

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
BUTANE	WEL	600 ppm		750 ppm		
ISOBUTANE	WEL	800 ppm		No std.		
OCTANE	SUP	300 ppm		375 ppm		

WEL = Workplace Exposure Limit.

#### **Ingredient Comments**

WEL = Workplace Exposure Limits

#### 8.2. Exposure controls

# FIXT Multipurpose Clear Fine Oil

#### **Engineering measures**

Provide adequate ventilation. Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of spray.

# Respiratory equipment

In case of inadequate ventilation use suitable respirator.

#### Hand protection

Due to the packaging form, aerosol, risk of skin contact is small. For prolonged or repeated skin contact use suitable protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material

#### Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable.

#### Hygiene measures

Wash hands after handling. Wash promptly if skin becomes contaminated. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin.

#### Personal protection

When using do not smoke

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

# 9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Odour Organic solvents.

Flash point (°C) <-40°C

Auto Ignition Temperature (°C) 410-580

Flammability Limit - Lower(%) 1.8

Flammability Limit - Upper(%) 9.5

**Comments** Information given concerns the major ingredient.

#### 9.2. Other information

#### **SECTION 10: STABILITY AND REACTIVITY**

# 10.1. Reactivity

#### 10.2. Chemical stability

Avoid Heat, sparks, flames.

# 10.3. Possibility of hazardous reactions

#### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

#### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

In case of fire, toxic gases (CO, CO2, NOx) may be formed.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

# 11.1. Information on toxicological effects

General information

Delibrately concentrating and inhaling the contents of this container is dangerous and can be fatal.

#### Inhalation

In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea. Unconsciousness, possibly death.

#### Skin contact

Skin irritation is not anticipated when used normally. Repeated exposure may cause skin dryness or cracking.

5 / 7

SDS No. 12436

# FIXT Multipurpose Clear Fine Oil

#### Eye contact

Spray and vapour in the eyes may cause irritation and smarting.

#### **Health Warnings**

Arrhythmia (deviation from normal heartbeat) Narcotic effect. Solvent vapours are hazardous and may cause nausea, sickness and headaches.

#### Route of entry

Inhalation.

#### **Target Organs**

Central nervous system Respiratory system, lungs

#### **Medical Symptoms**

Arrhythmia, (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness.

#### **SECTION 12: ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

ENVIRONMENTAL HAZARDS: This product has not been tested but contains ingredients which are harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment. During normal use the volatility of the components and the packaging form, pressurised container, make entry into the aquatic environment unlikely, however, do not empty or discharge into drains or watercourses. Ensure container is empty before disposal to prevent contents entering watercourses.

#### 12.1. Toxicity

#### 12.2. Persistence and degradability

#### 12.3. Bioaccumulative potential

#### 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

# **SECTION 13: DISPOSAL CONSIDERATIONS**

#### **General information**

Do not puncture or incinerate even when empty.

#### 13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk). Empty containers must not be burned because of explosion hazard.

#### **SECTION 14: TRANSPORT INFORMATION**

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and

IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities.

Aerosols not so packed and labelled must show the following.

# 14.1. UN number

 UN No. (ADR/RID/ADN)
 1950

 UN No. (IMDG)
 1950

 UN No. (ICAO)
 1950

#### 14.2. UN proper shipping name

Proper Shipping Name AEROSOLS.

# 14.3. Transport hazard class(es)

ADR/RID/ADN Class 2, 5F

# FIXT Multipurpose Clear Fine Oil

ADR/RID/ADN Class Class 2.1: Flammable gases.

ADR Label No. 3

IMDG Class 2.1

ICAO Class/Division 2.1

**Transport Labels** 



#### 14.4. Packing group

ADR/RID/ADN Packing group N/A

IMDG Packing group N/A

ICAO Packing group N/A

#### 14.5. Environmental hazards

#### 14.6. Special precautions for user

**EMS** 2-13

Hazard No. (ADR) 23 Flammable gas

Tunnel Restriction Code (D)

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

# **SECTION 15: REGULATORY INFORMATION**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# **Uk Regulatory References**

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. Chemicals (Hazard Information & Packaging) Regulations.

### Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health. The Aerosol Dispensers Regulations 1977 & 1999

#### **Approved Code Of Practice**

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply. British Aerosol Manufacturers Code of Practice 7th. Edition 1999

#### **Guidance Notes**

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

### **EU Legislation**

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC.

# National Regulations

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689.

#### 15.2. Chemical Safety Assessment

### **SECTION 16: OTHER INFORMATION**

SDS No. 12436
Safety Data Sheet Status Approved.
Date 15.04.2013

7 / 7

SDS No. 12436

# FIXT Multipurpose Clear Fine Oil

#### Risk Phrases In Full

R12 Extremely flammable.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R11 Highly flammable R38 Irritating to skin.

R67 Vapours may cause drowsiness and dizziness.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

# Hazard Statements In Full

H315 Causes skin irritation.

H222 Extremely flammable aerosol.
H220 Extremely flammable gas.

H412 Harmful to aquatic life with long lasting effects.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

H400 Very toxic to aquatic life.

#### Disclaimer