



SAFETY DATA SHEET
FIXT INSTANT POWER ADHESIVE HARDENER

Page: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: FIXT INSTANT POWER ADHESIVE HARDENER

Product code: FX085571

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Epoxy hardener preparation To be used in conjunction with Resin Pack

1.3. Details of the supplier of the safety data sheet

Supplier: Quest Consumables Limited
Seymour Road
Nuneaton
Warwickshire
CV11 4LB
Tel: 02476 322126
Fax: 02476 322117
Email: info@fixtconsumables.com

1.4. Emergency telephone number

Emergency tel: 02476 322126

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xn: R20/21; C: R34

Most important adverse effects: Harmful by inhalation and in contact with skin. Causes burns.

2.2. Label elements

Label elements under CHIP:

Hazard symbols: Corrosive.



Risk phrases: R20/21: Harmful by inhalation and in contact with skin.

R34: Causes burns.

Safety phrases: S1/2: Keep locked up and out of the reach of children.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

[cont...]

SAFETY DATA SHEET

FIXT INSTANT POWER ADHESIVE HARDENER

Page: 2

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

2.3. Other hazards

Other hazards: Causes severe irritation and burns to all tissues contacted. Harmful if swallowed or inhaled.

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

TETRAMETHYL BIS(AMINOETHYL) ETHER

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	3033-62-3	Xn: R22; T: R23/24; C: R35	-	1-5%

DIAZABICYCLO(5.4.0) UNDEC-7-ENE, 1, 8

-	6674-22-2	Xn: R22; C: R34; -: R52/53	-	1-5%
---	-----------	----------------------------	---	------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Immediately flush with plenty of water for at least 15 mins holding eyelids apart to ensure flushing of the entire surface. Washing within one minute is essential to achieve maximum effectiveness. Obtain medical attention.

Ingestion: Do not induce vomiting. Give large amounts of water followed by milk if available. If vomiting should occur spontaneously, keep airway clear. Get medical attention. Never give anything by mouth to an unconscious person.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Causes severe skin irritation or burns. Avoid contact

Eye contact: Causes severe irritation and burns. Possible permanent injury or blindness.

Ingestion: Can cause gastrointestinal tract irritation, nausea, vomiting, diarrhea and possible burns to mucous membranes.

Inhalation: Mist or vapour can cause respiratory tract irritation and possible burns to mucous membranes.

[cont...]

SAFETY DATA SHEET

FIXT INSTANT POWER ADHESIVE HARDENER

Page: 3

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Water spray. Carbon dioxide. Foam. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes. Cool fire-exposed containers with water.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Wear adequate protective clothing and equipment.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep at temperatures of between 5 and 40degC. Do not store together with epoxy constituents. Keep out of the reach of children.

[cont...]

SAFETY DATA SHEET

FIXT INSTANT POWER ADHESIVE HARDENER

Page: 4

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: Not applicable.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. If product is handled in an open system, the use of process enclosures, local exhaust ventilation, and/or other engineering controls should be considered to control airborne levels to below recommended exposure limits, or below acceptable levels.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Use a NIOSH approved full-face respirator with organic vapour acid gas cartridge when handling this material if warranted.

Hand protection: Wear chemical resistance gloves such as rubber, neoprene or vinyl, and work clothing with full length sleeves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow/Amber

Odour: Mercaptan-like odour

Solubility in water: Dispersible in water

Flash point°C: 93

Relative density: 1.12

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

[cont...]

SAFETY DATA SHEET

FIXT INSTANT POWER ADHESIVE HARDENER

Page: 5

10.4. Conditions to avoid

Conditions to avoid: None established.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide. In combustion emits toxic fumes of nitrogen oxides. In combustion emits toxic fumes of sulphur oxides.
Hydrogen sulphides

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
ORL	RAT	LD50	>3000	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH DRM	Hazardous: calculated
Corrosivity	OPT INH DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Causes severe skin irritation or burns. Avoid contact

Eye contact: Causes severe irritation and burns. Possible permanent injury or blindness.

Ingestion: Can cause gastrointestinal tract irritation, nausea, vomiting, diarrhea and possible burns to mucous membranes.

Inhalation: Mist or vapour can cause respiratory tract irritation and possible burns to mucous membranes.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

[cont...]

SAFETY DATA SHEET

FIXT INSTANT POWER ADHESIVE HARDENER

Page: 6

12.4. Mobility in soil

Mobility: No data available

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3267

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.(Mercaptan/amine Blend)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 1

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

[cont...]

SAFETY DATA SHEET

FIXT INSTANT POWER ADHESIVE HARDENER

Page: 7

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: R20/21: Harmful by inhalation and in contact with skin.

R22: Harmful if swallowed.

R23/24: Toxic by inhalation and in contact with skin.

R34: Causes burns.

R35: Causes severe burns.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.