



# Technical data sheet

## UNITRACK Universal Oil SUTO 10W-30 Multipurpose Agricultural Lubricant

### Description

UNITRACK Universal Oil SUTO 10W-30 offers versatility, performance and grade rationalisation opportunities in one product formulation. Product chemistry has been optimised for use in final drives, hydraulics, wet brakes, transmission and engines and will help to maintain component integrity and operational efficiency.

### Benefits:

- Single oil avoiding and reducing inventory costs
- Prolongs hardware and component longevity
- Outstanding wear, rust and corrosion protection
- Balanced friction performance gives precise clutch and brake operation

### Applications

May be used in a wide variety of applications, including:

- Tractors
- Combine harvesters
- Crop sprays and other ancillary equipment
- Materials handling equipment

### Performance Levels

Transmission and Driveline:	Engine:
MF M-1145 Approved	API CG-4/SF
MF M-1144 / M-1139	API CI-4 (Soot control*)
Ford M2C-159B / M2C-121B	MB 227.1
John Deere JDM J27	MB 228.3 (Wear protection* / Piston Cleanliness*)
ZF TE-ML 06B (includes C,Q,R)	MIL-L-2104D
ZF TE-ML 06D, 06F, 07B	
API GL-4	
Allison C4	
Caterpillar T-02	*Supporting data available

### Physical Characteristics

SAE Grade	10W-30
Density at 15 °C	0.871
Viscosity cSt at 100 °C	11.54
Viscosity cSt at 40 °C	74.31
Viscosity Index	149
Flash Point (closed) °C	165
Pour Point °C	-37
TBN	11.50

Figures based on average production values.

Part Nos. HLU1044  
Issue date: October 2025

HTS Spares, Surrey House, Beacon Road, Hereford, HR2 6JF  
T +44 (0) 1432 373 350 Email: [info@htsspares.com](mailto:info@htsspares.com)