



Technical Data Sheet

UTTO LV (1113)

Product Description

This modern multifunctional lubricating oil is specifically designed for agricultural and earthmoving equipment. It is formulated using top-quality solvent refined base oils and additives to provide the following characteristics: - A potent dispersion and detergency capability - A strong ability to combat wear, corrosion, and foam formation - Exceptional resistance to oxidation - Outstanding extreme pressure properties - A high and consistent viscosity index

Application

This versatile lubricant has been formulated to create a single lubricating oil that can effectively lubricate various components, including:

- Gasoline engines
- Diesel engines (with or without turbo-charging)
- Transmissions (including "wet" brakes)
- Hydraulic systems

This lubricant is commonly referred to as Super Tractor Oil Universal (STOU) due to its ability to cater to multiple functions.

Typical Properties

Density at 15 °C, kg/l 0,876	Viscosity 100 °C, mm ² /s 11,40
Viscosity -25 °C, mPa.s 4730	Viscosity Index 154
Viscosity 40 °C, mm ² /s 70,60	Flash Point COC, °C 228
Viscosity Index 155	Pour Point, °C -33
Total Base Number, mgKOH/g 11,3	Sulphate Ash, % 1,57

Specifications

API SF/CG-4/GL-4	Allison C4
ACEA E3, MIL-L-2104D	Cat TO-2
John Deere J27 / J20C	Ford M2C159-C / M2C134-D
ZF TE-ML 03E / 06K	Massey Ferguson CMS M1145 / M1144 / M1139
Massey Ferguson CMS M1143 / M1135	MB 227.1
NH 410B	ZF TE-ML 06B / 07B