

Lithium-Ion Battery Fire Extinguisher Range

Part Number: 3LFX / 6LFX / 9LFX

The LFX range has been specifically designed to tackle lithium-ion battery fires across a wide range of applications. In addition to primary fire risks, the LFX fluorine-free range of fire extinguishers also protect from secondary A-class fires that have been caused by the exploding batteries.

- Fluorine free foam concentrate
- 3ltr, 6ltr, 9ltr available
- Easy and ergonomic operation
- Economical maintenance and service
- 5 year manufacturer warranty



Specifications	3LFX	6LFX	9LFX
Agent	LFX	LFX	LFX
Capacity	3ltr	6ltr	9ltr
Fire Rating	Pending 13A	Pending 27A	Pending 34A
Working pressure (bar) @ 20°C	15	15	15
Maximum Service Pressure PS (bar)	20	20	20
Temperature Range °c	+5 to +60	+5 to +60	+5 to + 60
Discharge time (secs) @ 20°C	25-30	47-53	72-78
Cylinder	Lined Steel	Lined Steel	Lined Steel
Approved Certification	BS EN3 Kitemark, MED, MSR, PED, UKCA, CE	NTA 8133, BS EN3 Kitemark, MED, MSR, PED, UKCA, CE	NTA 8133, BS EN3 Kitemark, MED, MSR, PED, UKCA, CE
Dimensions (mm) (height x width x diameter)	435 x 285 x 145	568 x 300 x 170	622 x 265 x 190
Weight (kg)	5.8	10	14.3