Product Information: **MULTIVIS ADT VX 5W-30 SYNTHETIC TECHNOLOGY – MID-SAPS**



Description

Multivis ADT VX 5W-30 is a synthetic technology advanced lubricant, designed for use in the latest engines, including those fitted with exhaust gas after-treatment devices.

Multivis ADT VX 5W-30 has the following benefits:

- 1. Increased engine efficiency.
- 2. Outstanding fuel economy.
- 3. Provides extended oil drain capability.
- 4. Rapid cold start flow that reduces noise and wear.
- 5. Increased film strength at high temperatures under all driving conditions.
- 6. High temperature deposit and anti-sludge control.
- 7. Low levels of volatility.

Applications

Multivis ADT VX 5W-30 is recommended for the latest petrol and diesel engines, including turbocharged versions and those fitted with exhaust gas after-treatment devices such as particulate filters, catalytic converters, exhaust gas re-circulation, etc. Multivis ADT VX 5W-30 can be used where any of the following manufacturer's specifications are listed.

Performance Levels

VW 504.00/507.00 VW 503.00/503.01/506.00/506.01 ACEA C3 Porsche C30 MB 229.51 BMW Longlife-04 API SN

Physical Characteristics

Viscosity @ 100°C, cSt.	11.81
Viscosity @ 40 °C, cSt.	67.99
Viscosity Index	171
Density @ 15.6°C	0.850
Flash Point (Closed) °C	202
TBN, mg/KOH/g	6.5
Pour Point, °C	-42

Figures based on average production values.

Part No.s: VXC001, VXC005, VXC025, VXC060, VXC205

www.morrislubricants.co.uk



(TDS Multilife ADT VX 5W-30 – 051017 Issue 2)